

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision
Supersedes Version

3
2.00***

Revision Date
Issuing date

31-Jan-2022
31-Jan-2022

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Identification of the
substance/preparation

n-Butyl acetate

CAS-No
EC No.

123-86-4
204-658-1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance /
Preparation

solvent.

Uses advised against

None

1.3. Details of the supplier of the safety data sheet

Company/Undertaking
Identification

OQ Chemicals GmbH
Rheinpromenade 4A
D-40789 Monheim
Germany

OQ Chemicals Corporation
15375 Memorial Drive
West Memorial Place I
Suite 300
Houston, TX 77079
USA***

Product Information

Product Stewardship
FAX: +49 (0)208 693 2053
email: sc.psq@oq.com

1.4. Emergency telephone number

Emergency telephone number +44 (0) 1235 239 670 (UK) available 24/7
NCEC +1 202 464 2554

Local emergency telephone
number

+61 2 8014 4558 (Australia)
18000 74234 (Australia toll-free number)
+64 9 929 1483 (New Zealand)
0800 446 881 (New Zealand toll-free number)
+65 3158 1195 (Sri Lanka)
007 803 011 0293 (Indonesia toll-free number)
+60 3 6207 4347 (Malaysia)
001 800 120 666 751 (Thailand toll-free number)
+65 3158 1200 (Bangladesh)
+63 2 8231 2149 (Philippines)
+84 28 4458 2388 (Vietnam)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

+65 3165 2217 (Singapore)
available 24/7

SECTION 2: Hazards identification

Europe

2.1. Classification of the substance or mixture

This substance is classified based on Directive 1272/2008/EC and its amendments (CLP Regulation)

Flammable liquid Category 3, H226
Target Organ Systemic Toxicant - Single exposure Category 3, H336

Additional information

For full text of Hazard- and EU Hazard-statements see SECTION 16.

2.2. Label elements

Labelling according to Regulation 1272/2008/EC and its amendments (CLP Regulation).

Hazard pictograms



Signal word

Warning

Hazard statements

H226: Flammable liquid and vapour.
H336: May cause drowsiness or dizziness.

Precautionary statements

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P261: Avoid breathing gas/mist/vapours.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312: Call a POISON CENTRE/doctor if you feel unwell.
P403 + P235: Store in a well ventilated place. Keep cool.

Supplemental Hazard Information (EU)

EUH 066: Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

Vapours may form explosive mixture with air
Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

Components of the product may be absorbed into the body by inhalation

PBT and vPvB assessment This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

USA

2.1. Classification of the substance or mixture

This substance is classified in accordance with paragraph (d) of §1910.1200 (GHS-US classification).

Target Organ Systemic Toxicant - Single exposure Category 3, H336
Flammable liquid Category 3, H226
Environmental hazard Aquatic Acute 3; H402

OSHA Specified Hazards Not applicable.

2.2. Label elements

Labeling according to §1910.1200 (GHS-US labeling).

Hazard symbol(s)



Signal word

Warning

Hazard statements

H226: Flammable liquid and vapor.
H336: May cause drowsiness or dizziness.
H402: Harmful to aquatic life

Precautionary statements

Prevention

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233: Keep container tightly closed.
P240: Ground and bond container and receiving equipment.
P241: Use explosion-proof electrical/ ventilating/ lighting equipment.
P242: Use non-sparking tools.
P243: Take precautionary measures against static discharge.
P261: Avoid breathing gas/mist/vapours.
P271: Use only outdoors or in a well ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/eye protection/face protection.***

Response

P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

P312: Call a POISON CENTRE/doctor if you feel unwell.

Storage

P403 + P235: Store in a well ventilated place. Keep cool.
P405: Store locked up.

Disposal

P501: Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback
Vapours may form explosive mixture with air
Components of the product may be absorbed into the body by inhalation
Repeated exposure may cause skin dryness or cracking

SECTION 3: Composition / information on ingredients

3.1. Substances

Component	CAS-No	RECh-No	1272/2008/EC	Concentration (%)
n-Butyl acetate	123-86-4	01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 EU H066	> 99,0

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Keep at rest. Aerate with fresh air. When symptoms persist or in all cases of doubt seek medical advice.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

Skin

Wash off immediately with soap and plenty of water. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion

Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Main symptoms

cough, nausea, vomiting, headache, unconsciousness, shortness of breath, dizziness, narcosis.

Special hazard

Lung oedema, central nervous system effects, Prolonged skin contact may defat the skin and produce dermatitis.

4.3. Indication of any immediate medical attention and special treatment needed

General advice

Remove contaminated, soaked clothing immediately and dispose of safely. First aider needs to protect himself.

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

foam, dry chemical, carbon dioxide (CO₂), water spray

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Under conditions giving incomplete combustion, hazardous gases produced may consist of:

carbon monoxide (CO)

carbon dioxide (CO₂)

Combustion gases of organic materials must in principle be graded as inhalation poisons

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback

Vapours may form explosive mixture with air

5.3. Advice for firefighters

Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Keep people away from and upwind of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: For personal protective equipment see section 8. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.

For emergency responders: Personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

6.3. Methods and material for containment and cleaning up

Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

Methods for cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. If liquid has been spilt in large quantities clean up promptly by scoop or vacuum. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).



n-Butyl acetate
10430

Version / Revision 3

6.4. Reference to other sections

For personal protective equipment see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Advice on the protection of the environment

See Section 8: Environmental exposure controls.

Incompatible products

strong acids and strong bases
strong oxidizing agents

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material. Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback. Vapours may form explosive mixture with air.

Technical measures/Storage conditions

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care.

Suitable material

stainless steel, mild steel, aluminium

Unsuitable material

copper, Attacks some forms of plastic and rubber

Temperature class

T2

7.3. Specific end use(s)

Formulation
Distribution of substance
coatings
cleaning agent
laboratory chemicals

SECTION 8: Exposure controls / personal protection

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

8.1. Control parameters

Exposure limits European Union

Directive 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU ***

Component	TWA (mg/m ³)	TWA (ppm)	STEL (mg/m ³)	STEL (ppm)	Skin Absorption
n-Butyl acetate CAS: 123-86-4	241***	50***	723***	150***	

Exposure limits Germany

TRGS 900

Component	AGW (mg/m ³)	AGW (ppm)	STEL factor Peak factor	Peak-limit category
n-Butyl acetate CAS: 123-86-4	300	62	2	II
Component	Skin resorptive		Reproductive hazard	Note
n-Butyl acetate CAS: 123-86-4			Y	

MAK-values from the DFG

Component	MAK (ppm)	MAK (mg/m ³)	listed w/o limits	Ceiling limit value
n-Butyl acetate CAS: 123-86-4	100	480		(2) I
Component	H;S	carcinogenic category	pregnancy group	mutagenicity category
n-Butyl acetate CAS: 123-86-4			C	

Note

For details and further information please refer to the original regulation.

Exposure limits United States of America

US ACGIH

Component	TWA (mg/m ³)	TWA (ppm)	STEL (mg/m ³)	STEL (ppm)
n-Butyl acetate CAS: 123-86-4		50 ***		150

US OSHA Z-1

Component	Ceiling (mg/m ³)	Ceiling (ppm)	PEL (mg/m ³)	PEL (ppm)	Skin Designation
n-Butyl acetate CAS: 123-86-4			710	150	

Note

For details and further information please refer to the original regulation.

8.2. Exposure controls

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

Appropriate Engineering controls

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

Personal protective equipment

General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Ensure that eyewash stations and safety showers are close to the workstation location.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Hand protection

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

Suitable material	butyl-rubber
Evaluation	according to EN 374: level 3
Glove thickness	approx 0,3 mm
Break through time	approx 60 min

Suitable material	polyvinylchloride / nitrile rubber
Evaluation	according to EN 374: level 2
Glove thickness	approx 0,9 mm
Break through time	approx 30 min

Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

Respiratory protection

Respirator with filter for organic vapour. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Equipment should conform to NIOSH, EN or other applicable national standards.

Environmental exposure controls

If possible use in closed systems. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. Observe the exposure limits, clean exhaust air if needed. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	colourless
Odour	fruity
Odour threshold	7 - 20 ppm

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

pH 6,2 (5,3 g/l in water @ 20 °C (68 °F))
Melting point/range < -90 °C (Pour point)
Boiling point/range 126 °C @ 1013 hPa
Flash point 27 °C @ 1013 hPa
Method EU A.9
Evaporation rate 1,0 (n-Butyl acetate = 1)
Flammability (solid, gas) Does not apply, the substance is a liquid
Lower explosion limit 1,2 Vol %
Upper explosion limit 7,5 Vol %

Vapour pressure

Values [hPa]	Values [kPa]	Values [atm]	@ °C	@ °F	Method
11,2	1,12	0,0112	20	68	EU A.4***
57,9	5,79	0,0579	50	122	EU A.4***

Vapour density 4,0 (Air = 1) @ 20 °C (68 °F)

Relative density

Values	@ °C	@ °F	Method
0,881	20	68	DIN 51757

Solubility 5,3 g/l @ 20 °C, in water, OECD 105

log Pow 2,3 (measured) OECD 117

Autoignition temperature 415 °C @ 1013 hPa***

Method DIN 51794

Decomposition temperature No data available

Viscosity 0,83 mPa*s @ 20 °C

Method dynamic, OECD 114***

Oxidizing properties Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties

Explosive properties Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties

9.2. Other information

Molecular weight 116,16

Molecular formula C₆ H₁₂ O₂

log Koc 1,27 - 1,84 calculated***

Refractive index 1,393 @ 20 °C

Surface tension 61,3 mN/m (1 g/l @ 20°C (68°F)), OECD 115

SECTION 10: Stability and Reactivity

10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.

10.5. Incompatible materials

strong acids and strong bases, strong oxidizing agents.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure Ingestion, Inhalation, Eye contact, Skin contact

Acute toxicity				
n-Butyl acetate (123-86-4)				
Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	10760 mg/kg	rat, female***	OECD 423
Dermal	LD50	> 14112 mg/kg	rabbit	OECD 402
Inhalative	LC50	> 20 mg/l (4h)	rat***	Weight of evidence***

n-Butyl acetate, CAS: 123-86-4

Assessment

Based on available data, the classification criteria are not met for:

Acute oral toxicity

Acute dermal toxicity

Acute inhalation toxicity

Irritation and corrosion				
n-Butyl acetate (123-86-4)				
Target Organ Effects	Species	Result	Method	
Skin	rabbit	No skin irritation	OECD 404	
Eyes	rabbit	No eye irritation	OECD 405	
Respiratory tract	human	Low irritating potential		

n-Butyl acetate, CAS: 123-86-4

Assessment

Based on available data, the classification criteria are not met for:

skin irritation/corrosion

eye irritation/corrosion

respiratory irritation

Sensitization				
n-Butyl acetate (123-86-4)				
Target Organ Effects	Species	Evaluation	Method	
Skin	mouse	not sensitizing	MEST***	
Skin***	human***	not sensitizing***	Human repeat insult	

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

			patch test (HRIPT)***	
--	--	--	-----------------------	--

n-Butyl acetate, CAS: 123-86-4

Assessment

Based on available data, the classification criteria are not met for:

Skin sensitization

For respiratory sensitization, no data are available

Subacute, subchronic and prolonged toxicity

n-Butyl acetate (123-86-4)

Type	Dose	Species	Method	
Subchronic toxicity***	NOAEC: 500 ppm (90 d)***	rat, male/female	EPA OTS 798.2450	Inhalation
Subchronic toxicity***	NOAEL: 125 mg/kg/d (90d)***	rat, male/female	EPA OTS 798.2650***	Oral read across
Subchronic toxicity***	LOAEL: 500 mg/kg/d (90d)***	rat, male/female	EPA OTS 798.2650***	Oral read across

n-Butyl acetate, CAS: 123-86-4

Assessment

Based on available data, the classification criteria are not met for:

STOT RE

Carcinogenicity, Mutagenicity, Reproductive toxicity

n-Butyl acetate (123-86-4)

Type	Dose	Species	Evaluation	Method	
Mutagenicity		Salmonella typhimurium Escherichia coli***	negative	OECD 471 (Ames)	In vitro study***
Mutagenicity		CHL (Chinese hamster lung cells)	negative (without metabolic activation)	OECD 473 (Chromosomal Aberration) Chromosomal Aberration***	In vitro study
Mutagenicity		V79 cells, Chinese hamster	negative	OECD 476 (Mammalian Gene Mutation) HPRT	In vitro study read across
Mutagenicity		mouse	negative	OECD 474	in vivo read across
Reproductive toxicity	NOEC 9640 mg/m ³	rat, male/female***		OECD 416	
Developmental Toxicity	LOAEC: 7230 mg/m ³	rat, male/female***		OECD 414, Inhalative	Maternal toxicity Developmental toxicity
Developmental Toxicity***	NOAEC: 7230 mg/m ³ ***	rat, male/female***		OECD 414, Inhalative***	Maternal toxicity, Developmental toxicity, Teratogenicity***
Developmental Toxicity***	NOAEC: 7230 mg/m ³ ***	rabbit***		OECD 414, Inhalative***	Maternal toxicity Developmental

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

					toxicity***
Reproductive toxicity***	LOAEC: 750 ppm***	rat, male/female***		OECD 416 Inhalation***	Local effects***
Reproductive toxicity***	NOAEC: 750 ppm***	rat, male/female***		OECD 416 Inhalation***	systemic effects***
Reproductive toxicity***	NOAEC: 2000 ppm***	rat, male/female***		OECD 416 Inhalation***	Fertility***
Reproductive toxicity***	NOAEC: 750 ppm***	rat 2. Generation, male/female***		OECD 416 Inhalation***	Developmental toxicity***

n-Butyl acetate, CAS: 123-86-4

CMR Classification

The available data on CMR properties are summarized in the table above. They do not indicate a classification into categories 1A or 1B

Evaluation

Based on available data, the classification criteria are not met for:

Developmental toxicity

Reproductive toxicity

Mutagenicity

For carcinogenicity, no data are available***

n-Butyl acetate, CAS: 123-86-4

Main symptoms

dizziness, narcosis, cough, nausea, vomiting, headache, unconsciousness, shortness of breath.

Target Organ Systemic Toxicant - Single exposure

The available data lead to the classification given in section 2

Target Organ Systemic Toxicant - Repeated exposure

Repeated exposure may cause skin dryness or cracking

Based on available data, the classification criteria are not met for:

STOT RE

Other adverse effects

Components of the product may be absorbed into the body by inhalation.

Note

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link:

<http://echa.europa.eu/information-on-chemicals/registered-substances>.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity			
n-Butyl acetate (123-86-4)			
Species	Exposure time	Dose	Method
Pimephales promelas (fathead minnow)	96h	LC50: 18 mg/l	OECD 203
Pseudokirchneriella subcapitata***	72h	EC50: 397 mg/l (Growth rate)***	OECD 201 read across***
Tetrahymena pyriformis	40 h	IC50: 356 mg/l	
Daphnia magna (Water flea)	48h	EC50: 44 mg/l	OECD 202

Long term toxicity

n-Butyl acetate (123-86-4)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

Type	Species	Dose	Method	
Aquatic toxicity	Pseudokirchneriella subcapitata***	NOEC: 196 mg/l (3d)***	OECD 201 Growth rate	
Aquatic toxicity Reproductive toxicity	Daphnia magna (Water flea)	EC50: 34,2 mg/l/21d	OECD 211	read across
Aquatic toxicity Reproductive toxicity	Daphnia magna (Water flea)	NOEC: 23,2 mg/l (21d)***	OECD 211	read across

Terrestrial toxicity

n-Butyl acetate (123-86-4)

Species	Exposure time	Dose	Type	Method
Lactuca sativa (Lettuce)***	14 d***	EC50: > 1000 mg/kg soil dw***	Growth***	OECD 208***

12.2. Persistence and degradability

n-Butyl acetate, CAS: 123-86-4

Biodegradation

83 % (28 d), aerobic, Readily biodegradable, OECD 301 D.

Abiotic Degradation

n-Butyl acetate (123-86-4)

Type	Result	Method
Hydrolysis	t _{1/2} (pH 7): 2,14 yr @ 25°C	calculated***
Photolysis	Half-life (DT50): 3,3 days***	calculated***

12.3. Bioaccumulative potential

n-Butyl acetate (123-86-4)

Type	Result	Method
BCF	15,3	calculated
log Pow	2,3 @ 27 °C (77 °F)***	measured, OECD 117

12.4. Mobility in soil

n-Butyl acetate (123-86-4)

Type	Result	Method
Surface tension	61,3 mN/m (1 g/l @ 20°C (68°F))	OECD 115
Adsorption/Desorption	log K _{oc} : 1,27 - 1,84***	calculated
Distribution to environmental compartments	no data available	

12.5. Results of PBT and vPvB assessment

n-Butyl acetate, CAS: 123-86-4

PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

12.6. Other adverse effects

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

n-Butyl acetate, CAS: 123-86-4

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product Information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Hazardous waste according to European Waste Catalogue (EWC)

Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

ICAO-TI / IATA-DGR

14.1. UN number	UN 1123
14.2. UN proper shipping name	Butyl acetates
14.3. Transport hazard class(es)	3
14.4. Packing group	III
14.5. Environmental hazards	no
14.6. Special precautions for user	no data available

IMDG

14.1. UN number	UN 1123
14.2. UN proper shipping name	Butyl acetates
14.3. Transport hazard class(es)	3
14.4. Packing group	III
14.5. Environmental hazards	no
14.6. Special precautions for user	
EmS	F-E, S-D

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Product name	Butyl acetate
Ship type	3
Pollution category	Y

ADR/RID

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

14.1. UN number	UN 1123
14.2. UN proper shipping name	Butyl acetates
14.3. Transport hazard class(es)	3
14.4. Packing group	III
14.5. Environmental hazards	no
14.6. Special precautions for user	
ADR Tunnel restriction code	(D/E)
Classification Code	F1
Hazard Number	30

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation 1272/2008, Annex VI

n-Butyl acetate, CAS: 123-86-4

Classification	Flam. Liq. 3; H226 STOT SE 3; H336
Hazard pictograms	GHS02 Flame GHS07 Exclamation mark
Signal word	Warning
Hazard statements	H226, H336 EUH066

DI 2012/18/EU (Seveso III)

Category	Annex I, part 1: P5a - c; depending on conditions
-----------------	--

DI 1999/13/EC (VOC Guideline)

Component	Status
n-Butyl acetate CAS: 123-86-4	regulated

International Inventories

n-Butyl acetate, CAS: 123-86-4

AICS (AU)
DSL (CA)
IECSC (CN)
EC-No. 2046581 (EU)
ENCS (2)-731 (JP)
ISHL (2)-731 (JP)
ISHL 2-(6)-226 (JP)
KECI KE-04179 (KR)
INSQ (MX)
PICCS (PH)
TSCA (US)
NZIoC (NZ)

SAFETY DATA SHEET



n-Butyl acetate
10430

Version / Revision 3

TCSI (TW)

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

EUH 066: Repeated exposure may cause skin dryness or cracking.

Abbreviations

A table of terms and abbreviations can be found under the following link:

http://echa.europa.eu/documents/10162/13632/information_requirements_r20_en.pdf

Training advice

For effective first-aid, special training / education is needed.

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on OQ owned data and public sources deemed valid or acceptable. The absence of data elements required by OSHA, ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

Further information for the safety data sheet

Changes against the previous version are marked by ***. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the OQ homepage (www.chemicals.oq.com).

Disclaimer

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. OQ makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

End of Safety Data Sheet