



# Sales Specification

## Propionaldehyde (manufactured in USA)

### General data

**CAS-No.** 123-38-6 **Version** 2  
**Date of issue** 16.06.2020  
**Product No.** 50000864 51006723  
Additional product number(s) may be in use for other packaging

### Sales Specification

Property	Limit	Unit	Test Method
Propionaldehyde *)	min. 98.5	% (w/w)	Gas chromatography
Water	max. 0.4	% (w/w)	Gas chromatography / DIN 51777 (mod. Karl-Fischer-Method)
Acidity, as Acetic acid	max. 0.2	% (w/w)	DIN EN ISO 2114 / ASTM D1613
Platinum/Cobalt Color (Hazen/APHA Color)	max. 20		DIN EN 1557 / DIN EN ISO 6271 / ASTM D1209

**Remarks** \*) By difference: 100.0% minus water, acidity and impurities determined by Gas chromatography (GC)

The parameters given in the Sales Specification table are listed on the Product Quality Report (PQR).  
Non-standard Test methods used are available upon request (due to Copy Right). Contact your Sales Support for copies.

Page 1 of 1  
10640 US OQ SLS EN V2.docx

Typical properties not especially listed are given in the appropriate SDS, they are not part of the sales specification.

This information is based on our present state of knowledge and shall be intended to provide general notes on our products and their field of application. It shall therefore not be construed as guaranteeing specific characteristics of the products described and/or their suitability for a particular application. Any existing industrial property rights shall be observed. The quality of our products is warranted under our General Conditions of Sale.