

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



n-Butyl acetate  
10430

Version / Revision  
Supersedes Version

9  
8.00\*\*\*

Revision Date  
Issuing date

27-Oct-2022  
27-Oct-2022

## SECTION 1: Identification of the substance / mixture and of the company / undertaking

### 1.1. Product identifier

Identification of the  
substance/preparation

**n-Butyl acetate**

CAS-No  
EC No.

123-86-4  
204-658-1

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Formulation  
Distribution of substance  
coatings  
cleaning agent  
laboratory chemicals

Uses advised against

None

### 1.3. Details of the supplier of the safety data sheet

Company/Undertaking  
Identification

**OQ Chemicals GmbH**  
Rheinpromenade 4A  
D-40789 Monheim  
Germany

Product Information

Product Stewardship  
FAX: +49 (0)208 693 2053  
email: sc.psq@oq.com

### 1.4. Emergency telephone number

Emergency telephone number +44 (0) 1235 239 670 (UK)  
available 24/7

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

This substance is classified based on Directive 1272/2008/EC and its amendments (CLP Regulation)

Flammable liquid Category 3, H226

Target Organ Systemic Toxicant - Single exposure Category 3, H336

#### Additional information

For full text of Hazard- and EU Hazard-statements see SECTION 16.

### 2.2. Label elements

Labelling according to Regulation 1272/2008/EC and its amendments (CLP Regulation).

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



n-Butyl acetate  
10430

Version / Revision 9

## Hazard pictograms



### Signal word

### Warning

### Hazard statements

H226: Flammable liquid and vapour.  
H336: May cause drowsiness or dizziness.

### Precautionary statements

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233: Keep container tightly closed.  
P261: Avoid breathing gas/mist/vapours.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312: Call a POISON CENTRE/doctor if you feel unwell.  
P403 + P235: Store in a well ventilated place. Keep cool.

### Supplemental Hazard Information (EU)

EUH 066: Repeated exposure may cause skin dryness or cracking.

## 2.3. Other hazards

Vapours may form explosive mixture with air  
Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback  
Components of the product may be absorbed into the body by inhalation

### PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

### Endocrine disrupting assessments

The substance is not listed on the candidate list according to Art. 59(1), REACH. The substance was not assessed as having endocrine disrupting properties according to regulation 2017/2100/EU or 2018/605/EU.

## SECTION 3: Composition / information on ingredients

### 3.1. Substances

Component	CAS-No	1272/2008/EC	Concentration (%)
n-Butyl acetate	123-86-4	Flam. Liq. 3; H226 STOT SE 3; H336 EU H066	> 99,0

For full text of Hazard- and EU Hazard-statements see SECTION 16.

## SECTION 4: First aid measures

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## 4.1. Description of first aid measures

### Inhalation

Keep at rest. Aerate with fresh air. When symptoms persist or in all cases of doubt seek medical advice.

### Skin

Wash off immediately with soap and plenty of water. When symptoms persist or in all cases of doubt seek medical advice.

### Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

### Ingestion

Call a physician immediately. Do not induce vomiting without medical advice.

## 4.2. Most important symptoms and effects, both acute and delayed

### Main symptoms

cough, nausea, vomiting, headache, unconsciousness, shortness of breath, dizziness, narcosis.

### Special hazard

Lung oedema, central nervous system effects, Prolonged skin contact may defat the skin and produce dermatitis.

## 4.3. Indication of any immediate medical attention and special treatment needed

### General advice

Remove contaminated, soaked clothing immediately and dispose of safely. First aider needs to protect himself.

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water spray

#### Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

Under conditions giving incomplete combustion, hazardous gases produced may consist of:

carbon monoxide (CO)

carbon dioxide (CO<sub>2</sub>)

Combustion gases of organic materials must in principle be graded as inhalation poisons

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback

Vapours may form explosive mixture with air

### 5.3. Advice for firefighters

#### Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Keep people away from and upwind of fire.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: For personal protective equipment see section 8. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.

For emergency responders: Personal protection see section 8.

### 6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

### 6.3. Methods and material for containment and cleaning up

#### Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

#### Methods for cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. If liquid has been spilt in large quantities clean up promptly by scoop or vacuum. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

### 6.4. Reference to other sections

For personal protective equipment see section 8.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Further info may be available in the appropriate Exposure scenarios in the annex to this SDS.

#### Advice on safe handling

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms.

#### Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

#### Advice on the protection of the environment

See Section 8: Environmental exposure controls.

#### Incompatible products

strong acids and strong bases  
strong oxidizing agents

### 7.2. Conditions for safe storage, including any incompatibilities

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material. Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback. Vapours may form explosive mixture with air.

## Technical measures/Storage conditions

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care.

## Suitable material

stainless steel, mild steel, aluminium

## Unsuitable material

copper, Attacks some forms of plastic and rubber

## Temperature class

T2

## 7.3. Specific end use(s)

Formulation

Distribution of substance

coatings

cleaning agent

laboratory chemicals

For specific end use information see the annex of this safety data sheet

## SECTION 8: Exposure controls / personal protection

### 8.1. Control parameters

#### Exposure limits European Union

Directive 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Component	TWA (mg/m <sup>3</sup> )	TWA (ppm)	STEL (mg/m <sup>3</sup> )	STEL (ppm)	Skin Absorption
n-Butyl acetate CAS: 123-86-4	241	50	723	150	

#### Exposure limits UK

##### EH40 WELs

Component	TWA (mg/m <sup>3</sup> )	TWA (ppm)	STEL (mg/m <sup>3</sup> )	STEL (ppm)
n-Butyl acetate CAS: 123-86-4	724	150	966	200

#### Note

For details and further information please refer to the original regulation.

#### DNEL & PNEC

#### n-Butyl acetate, CAS: 123-86-4

#### Workers

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



n-Butyl acetate  
10430

Version / Revision 9

DN(M)EL - long-term exposure - systemic effects - Inhalation	300 mg/m <sup>3</sup>
DN(M)EL - acute / short-term exposure - systemic effects - Inhalation	600 mg/m <sup>3</sup>
DN(M)EL - long-term exposure - local effects - Inhalation	300 mg/m <sup>3</sup>
DN(M)EL - acute / short-term exposure - local effects - Inhalation	600 mg/m <sup>3</sup>
DN(M)EL - long-term exposure - systemic effects - Dermal	11 mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Dermal	11 mg/kg bw/day
DN(M)EL - long-term exposure - local effects - Dermal	No hazard identified
DN(M)EL - acute / short-term exposure - local effects - Dermal	No hazard identified
DN(M)EL - local effects - eyes	No hazard identified

## General population

DN(M)EL - long-term exposure - systemic effects - Inhalation	35,7 mg/m <sup>3</sup>
DN(M)EL - acute / short-term exposure - systemic effects - Inhalation	300 mg/m <sup>3</sup>
DN(M)EL - long-term exposure - local effects - Inhalation	35,7 mg/m <sup>3</sup>
DN(M)EL - acute / short-term exposure - local effects - Inhalation	300 mg/m <sup>3</sup>
DN(M)EL - long-term exposure - systemic effects - Dermal	6 mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Dermal	6 mg/kg bw/day
DN(M)EL - long-term exposure - local effects - Dermal	No hazard identified
DN(M)EL - acute / short-term exposure - local effects - Dermal	No hazard identified
DN(M)EL - long-term exposure - systemic effects - Oral	2 mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Oral	2 mg/kg bw/day
DN(M)EL - local effects - eyes	No hazard identified

## Environment

PNEC aqua - freshwater	0,18 mg/l
PNEC aqua - marine water	0,018 mg/l
PNEC aqua - intermittent releases	0,36 mg/l
PNEC STP	35,6 mg/l
PNEC sediment - freshwater	0,981 mg/kg
PNEC sediment - marine water	0,0981 mg/l
PNEC Air	No hazard identified
PNEC soil	0,0903 mg/kg
Secondary poisoning	No potential for bioaccumulation

## 8.2. Exposure controls

### Special adaptations (REACH)

Not applicable.

### Appropriate Engineering controls

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

### Personal protective equipment

#### General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Ensure that eyewash stations and safety showers are close to the workstation location.

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

## Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Equipment should conform to EN 166

## Hand protection

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

<b>Suitable material</b>	butyl-rubber
<b>Evaluation</b>	according to EN 374: level 3
<b>Glove thickness</b>	approx 0,3 mm
<b>Break through time</b>	approx 60 min

<b>Suitable material</b>	polyvinylchloride / nitrile rubber
<b>Evaluation</b>	according to EN 374: level 2
<b>Glove thickness</b>	approx 0,9 mm
<b>Break through time</b>	approx 30 min

## Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

## Respiratory protection

Respirator with A filter. Full mask with above mentioned filter according to producers using requirements or self-contained breathing apparatus. Equipment should conform to EN 136 or EN 140 and EN 143.

## Environmental exposure controls

If possible use in closed systems. If leakage can not be prevented, the substance needs to be suck off at the emission point, if possible without danger. Observe the exposure limits, clean exhaust air if needed. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

## Additional advice

Further details on substance data can be found in the registration dossier under the following link:  
<http://echa.europa.eu/information-on-chemicals/registered-substances>. For specific exposure controls see the annex to this safety data sheet.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	liquid***
<b>Colour</b>	colourless
<b>Odour</b>	fruity
<b>Odour threshold</b>	7 - 20 ppm
<b>Melting point/freezing point</b>	< -90 °C (Pour point)
<b>Method</b>	DIN ISO 3016
<b>Boiling point or initial boiling point and boiling range</b>	126 °C @ 1013 hPa
<b>Method</b>	OECD 103
<b>Flammability</b>	Ignitable

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

<b>Lower explosion limit</b>	1,2 Vol %				
<b>Upper explosion limit</b>	7,5 Vol %				
<b>Flash point</b>	27 °C @ 1013 hPa				
<b>Method</b>	EU A.9				
<b>Autoignition temperature</b>	415 °C @ 1013 hPa				
<b>Method</b>	DIN 51794				
<b>Decomposition temperature</b>	No data available				
<b>pH</b>	6,2 (5,3 g/l in water @ 20 °C (68 °F))				
<b>Kinematic Viscosity</b>	0,942 mm <sup>2</sup> /s @ 20 °C***				
<b>Method</b>	OECD 114***				
<b>Solubility</b>	5,3 g/l @ 20 °C, in water, OECD 105				
<b>Partition coefficient</b>	2,3 (measured) OECD 117				
<b>n-octanol/water (log value)</b>					
<b>Vapour pressure</b>					
Values [hPa]	Values [kPa]	Values [atm]	@ °C	@ °F	Method
11,2	1,12	0,0112	20	68	EU A.4
57,9	5,79	0,0579	50	122	EU A.4
<b>Density and/or relative density</b>					
Values	@ °C	@ °F	Method		
0,881	20	68	DIN 51757		
<b>Relative vapour density</b>	4,0 (Air = 1) @ 20 °C (68 °F)				
<b>Particle characteristics</b>	not applicable				

## 9.2. Other information

<b>Explosive properties</b>	Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties
<b>Oxidizing properties</b>	Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties
<b>Molecular weight</b>	116,16
<b>Molecular formula</b>	C <sub>6</sub> H <sub>12</sub> O <sub>2</sub>
<b>log K<sub>oc</sub></b>	1,27 - 1,84 calculated
<b>Refractive index</b>	1,393 @ 20 °C
<b>Surface tension</b>	61,3 mN/m (1 g/l @ 20°C (68°F)), OECD 115
<b>Evaporation rate</b>	1,0 (n-Butyl acetate = 1)

## SECTION 10: Stability and Reactivity

### 10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

### 10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.



# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## 10.5. Incompatible materials

strong acids and strong bases, strong oxidizing agents.

## 10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Likely routes of exposure**      Ingestion, Inhalation, Eye contact, Skin contact

<b>Acute toxicity</b>				
<b>n-Butyl acetate (123-86-4)</b>				
Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	10760 mg/kg	rat, female	OECD 423
Dermal	LD50	> 14112 mg/kg	rabbit	OECD 402
Inhalative	LC50	> 20 mg/l (4h)	rat	Weight of evidence

#### **n-Butyl acetate, CAS: 123-86-4**

##### **Assessment**

Based on available data, the classification criteria are not met for:

Acute oral toxicity  
Acute dermal toxicity  
Acute inhalation toxicity

<b>Irritation and corrosion</b>				
<b>n-Butyl acetate (123-86-4)</b>				
Target Organ Effects	Species	Result	Method	
Skin	rabbit	No skin irritation	OECD 404	
Eyes	rabbit	No eye irritation	OECD 405	
Respiratory tract	human	Low irritating potential		

#### **n-Butyl acetate, CAS: 123-86-4**

##### **Assessment**

Based on available data, the classification criteria are not met for:

skin irritation/corrosion  
eye irritation/corrosion  
respiratory irritation

<b>Sensitization</b>				
<b>n-Butyl acetate (123-86-4)</b>				
Target Organ Effects	Species	Evaluation	Method	
Skin	mouse	not sensitizing	MEST	
Skin	human	not sensitizing	Human repeat insult patch test (HRIPT)	

#### **n-Butyl acetate, CAS: 123-86-4**

##### **Assessment**

Based on available data, the classification criteria are not met for:

Skin sensitization

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

For respiratory sensitization, no data are available

<b>Subacute, subchronic and prolonged toxicity</b>				
<b>n-Butyl acetate (123-86-4)</b>				
Type	Dose	Species	Method	
Subchronic toxicity	NOAEC: 500 ppm (90 d)	rat, male/female	EPA OTS 798.2450	Inhalation
Subchronic toxicity	NOAEL: 125 mg/kg/d (90d)	rat, male/female	EPA OTS 798.2650	Oral read across
Subchronic toxicity	LOAEL: 500 mg/kg/d (90d)	rat, male/female	EPA OTS 798.2650	Oral read across

## **n-Butyl acetate, CAS: 123-86-4**

### **Assessment**

Based on available data, the classification criteria are not met for:  
STOT RE

<b>Carcinogenicity, Mutagenicity, Reproductive toxicity</b>					
<b>n-Butyl acetate (123-86-4)</b>					
Type	Dose	Species	Evaluation	Method	
Mutagenicity		Salmonella typhimurium Escherichia coli	negative	OECD 471 (Ames)	In vitro study
Mutagenicity		CHL (Chinese hamster lung cells)	negative (without metabolic activation)	OECD 473 (Chromosomal Aberration) Chromosomal Aberration	In vitro study
Mutagenicity		V79 cells, Chinese hamster	negative	OECD 476 (Mammalian Gene Mutation) HPRT	In vitro study read across
Mutagenicity		mouse	negative	OECD 474	in vivo read across
Reproductive toxicity	NOEC 9640 mg/m <sup>3</sup>	rat, male/female		OECD 416	
Developmental Toxicity	LOAEC: 7230 mg/m <sup>3</sup>	rat, male/female		OECD 414, Inhalative	Maternal toxicity Developmental toxicity
Developmental Toxicity	NOAEC: 7230 mg/m <sup>3</sup>	rat, male/female		OECD 414, Inhalative	Maternal toxicity, Developmental toxicity, Teratogenicity
Developmental Toxicity	NOAEC: 7230 mg/m <sup>3</sup>	rabbit		OECD 414, Inhalative	Maternal toxicity Developmental toxicity
Reproductive toxicity	LOAEC: 750 ppm	rat, male/female		OECD 416 Inhalation	Local effects
Reproductive toxicity	NOAEC: 750 ppm	rat, male/female		OECD 416 Inhalation	systemic effects
Reproductive toxicity	NOAEC: 2000 ppm	rat, male/female		OECD 416 Inhalation	Fertility
Reproductive toxicity	NOAEC: 750 ppm	rat 2. Generation, male/female		OECD 416 Inhalation	Developmental toxicity

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## n-Butyl acetate, CAS: 123-86-4

### CMR Classification

The available data on CMR properties are summarized in the table above. They do not indicate a classification into categories 1A or 1B

### Evaluation

Based on available data, the classification criteria are not met for:

Developmental toxicity

Reproductive toxicity

Mutagenicity

For carcinogenicity, no data are available

## n-Butyl acetate, CAS: 123-86-4

### Main symptoms

dizziness, narcosis, cough, nausea, vomiting, headache, unconsciousness, shortness of breath.

### Target Organ Systemic Toxicant - Single exposure

The available data lead to the classification given in section 2

### Target Organ Systemic Toxicant - Repeated exposure

Repeated exposure may cause skin dryness or cracking

Based on available data, the classification criteria are not met for:

STOT RE

## 11.2. Information on other hazards

### Endocrine disrupting properties

The substance has not been identified as having endocrine disrupting properties in accordance with section 2.3.

## n-Butyl acetate, CAS: 123-86-4

### Other adverse effects

Components of the product may be absorbed into the body by inhalation.

### Note

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link:

<http://echa.europa.eu/information-on-chemicals/registered-substances>.

## SECTION 12: Ecological information

### 12.1. Toxicity

Acute aquatic toxicity			
n-Butyl acetate (123-86-4)			
Species	Exposure time	Dose	Method
Pimephales promelas (fathead minnow)	96h	LC50: 18 mg/l	OECD 203
Pseudokirchneriella subcapitata	72h	EC50: 397 mg/l (Growth rate)	OECD 201 read across
Tetrahymena pyriformis	40 h	IC50: 356 mg/l	
Daphnia magna (Water flea)	48h	EC50: 44 mg/l	OECD 202

Long term toxicity				
n-Butyl acetate (123-86-4)				
Type	Species	Dose	Method	
Aquatic toxicity	Pseudokirchneriella subcapitata	NOEC: 196 mg/l (3d)	OECD 201 Growth rate	
Aquatic toxicity	Daphnia magna	EC50: 34,2 mg/l/21d	OECD 211	read across

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

Reproductive toxicity	(Water flea)			
Aquatic toxicity	Daphnia magna	NOEC: 23,2 mg/l	OECD 211	read across
Reproductive toxicity	(Water flea)	(21d)		

## Terrestrial toxicity

### **n-Butyl acetate (123-86-4)**

Species	Exposure time	Dose	Type	Method
Lactuca sativa (Lettuce)	14 d	EC50: > 1000 mg/kg soil dw	Growth	OECD 208

## 12.2. Persistence and degradability

### **n-Butyl acetate, CAS: 123-86-4**

#### Biodegradation

83 % (28 d), aerobic, Readily biodegradable, OECD 301 D.

#### Abiotic Degradation

### **n-Butyl acetate (123-86-4)**

Type	Result	Method
Hydrolysis	t <sub>1/2</sub> (pH 7): 2,14 yr @ 25°C	calculated
Photolysis	Half-life (DT50): 3,3 days	calculated

## 12.3. Bioaccumulative potential

### **n-Butyl acetate (123-86-4)**

Type	Result	Method
BCF	15,3	calculated
log Pow	2,3 @ 27 °C (77 °F)	measured, OECD 117

## 12.4. Mobility in soil

### **n-Butyl acetate (123-86-4)**

Type	Result	Method
Surface tension	61,3 mN/m (1 g/l @ 20°C (68°F))	OECD 115
Adsorption/Desorption	log K <sub>oc</sub> : 1,27 - 1,84	calculated
Distribution to environmental compartments	no data available	

## 12.5. Results of PBT and vPvB assessment

### **n-Butyl acetate, CAS: 123-86-4**

#### PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

## 12.6. Endocrine disrupting properties

The substance has not been identified as having endocrine disrupting properties in accordance with section 2.3.

## 12.7. Other adverse effects

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

**n-Butyl acetate, CAS: 123-86-4**

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Product Information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Hazardous waste according to European Waste Catalogue (EWC)

#### Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

## SECTION 14: Transport information

### ADR/RID

<b>14.1. UN number or ID number</b>	UN 1123
<b>14.2. UN proper shipping name</b>	Butyl acetates
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	III
<b>14.5. Environmental hazards</b>	no
<b>14.6. Special precautions for user</b>	
ADR Tunnel restriction code	(D/E)
Classification Code	F1
Hazard Number	30

### ADN

ADN Container

<b>14.1. UN number or ID number</b>	UN 1123
<b>14.2. UN proper shipping name</b>	Butyl acetates
<b>14.3. Transport hazard class(es)</b>	3
<b>14.4. Packing group</b>	III
<b>14.5. Environmental hazards</b>	no
<b>14.6. Special precautions for user</b>	
Classification Code	F1
Hazard Number	30

### ADN

ADN Tanker

<b>14.1. UN number or ID number</b>	UN 1123
<b>14.2. UN proper shipping name</b>	Butyl acetates
<b>14.3. Transport hazard class(es)</b>	3
Subsidiary Risk	N3
<b>14.4. Packing group</b>	III

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



n-Butyl acetate  
10430

Version / Revision 9

**14.5. Environmental hazards** no

**14.6. Special precautions for user**  
Classification Code F1

## ICAO-TI / IATA-DGR

**14.1. UN number or ID number** UN 1123  
**14.2. UN proper shipping name** Butyl acetates  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III  
**14.5. Environmental hazards** no  
**14.6. Special precautions for user** no data available

## IMDG

**14.1. UN number or ID number** UN 1123  
**14.2. UN proper shipping name** Butyl acetates  
**14.3. Transport hazard class(es)** 3  
**14.4. Packing group** III  
**14.5. Environmental hazards** no  
**14.6. Special precautions for user**  
EmS F-E, S-D  
\*\*\*  
**14.7. Maritime transport in bulk according to IMO instruments**  
Product name Butyl acetate  
Ship type 3  
Pollution category Y  
Hazard class P\*\*\*

## **SECTION 15: Regulatory information**

### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

#### Regulation 1272/2008, Annex VI

##### n-Butyl acetate, CAS: 123-86-4

**Classification** Flam. Liq. 3; H226  
STOT SE 3; H336  
**Hazard pictograms** GHS02 Flame  
GHS07 Exclamation mark  
**Signal word** Warning  
**Hazard statements** H226, H336  
EUH066

##### DI 2012/18/EU (Seveso III)

**Category** Annex I, part 1:  
P5a - c; depending on conditions

##### DI 1999/13/EC (VOC Guideline)

Component	Status
-----------	--------

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

n-Butyl acetate CAS: 123-86-4	regulated
----------------------------------	-----------

## **The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 No. 758**

<b>Component</b>	<b>Status</b>
n-Butyl acetate CAS: 123-86-4	The substance is/will be pre-registered

For details and further information please refer to the original regulation.

## **International Inventories**

### **n-Butyl acetate, CAS: 123-86-4**

AICS (AU)  
DSL (CA)  
IECSC (CN)  
EC-No. 2046581 (EU)  
ENCS (2)-731 (JP)  
ISHL (2)-731 (JP)  
ISHL 2-(6)-226 (JP)  
KECI KE-04179 (KR)  
INSQ (MX)  
PICCS (PH)  
TSCA (US)  
NZIoC (NZ)  
TCSI (TW)

## **National regulatory information Great Britain**

### **Releases to air (Pollution Inventory Substances)**

not subject

### **Releases to water (Pollution Inventory Substances)**

not subject

### **Releases to sewer (Pollution Inventory Substances)**

not subject

For details and further information please refer to the original regulation

## **15.2. Chemical safety assessment**

The Chemical Safety Report (CSR) has been generated. For Exposure Scenarios see the annex.

## **SECTION 16: Other information**

### **Full text of H-Statements referred to under sections 2 and 3**

H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

EUH 066: Repeated exposure may cause skin dryness or cracking.

### **Abbreviations**

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

A table of terms and abbreviations can be found under the following link:  
[http://echa.europa.eu/documents/10162/13632/information\\_requirements\\_r20\\_en.pdf](http://echa.europa.eu/documents/10162/13632/information_requirements_r20_en.pdf)

## Training advice

For effective first-aid, special training / education is needed.

## Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on OQ owned data and public sources deemed valid or acceptable. The absence of data elements required by OSHA, ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

## Further information for the safety data sheet

Changes against the previous version are marked by \*\*\*. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the OQ homepage ([www.chemicals.oq.com](http://www.chemicals.oq.com)).

## Disclaimer

**For industrial use only.** The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. OQ Chemicals makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

**End of Safety Data Sheet**

# Annex to the extended Safety Data Sheet (eSDS)

## General information

Risks resulting from short-term exposure are covered by the long-term exposure assessment  
For consumer applications in the following usage areas please contact OQ ([sc.psq@oq.com](mailto:sc.psq@oq.com)):

Uses in coatings

Use in Cleaning Agents

Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances (PC39, SU21).

Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described below and you are unsure if they are also safe

For specific information regarding the SPERC used please refer to the ESIG webpage  
<https://www.esig.org/reach-ges/environment/>

## Exposure scenario identification

- 1 Formulation & (re)packing of substances and mixtures**
- 2 Distribution of substance**
- 3 Uses in coatings**
- 4 Uses in coatings**
- 5 Use in Cleaning Products**
- 6 Use in Cleaning Products**



# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

**7 Use in laboratories**  
**8 Use in laboratories**

**Number of the ES** 1

Short title of the exposure scenario

**Formulation & (re)packing of substances and mixtures**

**List of use descriptors**

## **Sector of uses [SU]**

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites  
SU10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

## **Process categories [PROC]**

PROC1: Use in closed process, no likelihood of exposure  
PROC2: Use in closed, continuous process with occasional controlled exposure  
PROC3: Use in closed batch process (synthesis or formulation)  
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises  
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)  
PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities  
PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities  
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)  
PROC14: production of preparations or articles by tableting, compression, extrusion, pelettisation  
PROC15: Use as laboratory reagent

## **Environmental release categories [ERC]**

ERC2: Formulation of preparations (mixtures)

## **Product characteristics**

Refer to attached safety data sheets

## **Processes and activities covered by the exposure scenario**

Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

## **Further explanations**

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes an advanced standard of occupational Health and Safety Management System

## **Contributing Scenarios**

**Number of the contributing scenario**

1

**Contributing exposure scenario controlling environmental exposure for ERC 2**

## **Further specification**

SpERC ESVOC 2.2.v1 (ESVOC 4), release factors for (Sp)ERC were modified, assessment tool used: Chesar 2.3.

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Product characteristics

liquid.

### Amounts used

Daily amount per site: 13.33 to

Annual amount per site: 4000 to

Fraction of Regional tonnage used locally: 1

### Frequency and duration of use

Covers use up to: 300 days

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d

### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 2.5 %

Release fraction to wastewater from process: 0.05 %

Release fraction to soil from process: 0.01%

### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 90 %

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

Estimated substance removal from wastewater via domestic sewage treatment (%): 88.9

Do not apply industrial sludge to natural soils

**Number of the contributing scenario** 2

**Contributing exposure scenario controlling worker exposure for PROC 1**

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 3

**Contributing exposure scenario controlling worker exposure for PROC 2**

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 4

**Contributing exposure scenario controlling worker exposure for PROC 3**

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 5

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 8b

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 9

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Number of the contributing scenario

10

## Contributing exposure scenario controlling worker exposure for PROC 14

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Number of the contributing scenario

11

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.037 mg/l; RCR: 0.208
Fresh Water (Sediment)	PEC: 0.75 mg/kg dw; RCR: 0.765
Marine Water (Pelagic)	PEC: 0.004 mg/l; RCR: 0.208
Marine Water (Sediment)	PEC: 0.075 mg/kg dw; RCR: 0.764
Agricultural Soil	PEC: 0.012 mg/kg dw; RCR: 0.129
Sewage Treatment Plant (Effluent)	PEC: 0.372 mg/l; RCR: 0.01
Man via environment – Inhalation	Concentration in air: 0.076 mg/m <sup>3</sup> ; RCR: 0.01
Man via environment – Oral	Exposure via food consumption: 0.002 mg/kg bw/day; RCR: 0.01

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d].

Proc 1	EE(inhal): 0.194 ; EE(derm): 0.034
Proc 2	EE(inhal): 96.8 ; EE(derm): 1.37
Proc 3	EE(inhal): 193.6 ; EE(derm): 0.69
Proc 4	EE(inhal): 387.2; EE(derm): 1.372
Proc 5	EE(inhal): 96.8 ; EE(derm): 2.742
Proc 8a	EE(inhal): 96.8; EE(derm): 2.742
Proc 8b	EE(inhal): 484 ; EE(derm): 1.371
Proc 9	EE(inhal): 96.8 ; EE(derm): 6.86
Proc 14	EE(inhal): 96.8 ; EE(derm): 3.43
Proc 15	EE(inhal): 193.6 ; EE(derm): 0.34

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

Proc 1	RCR(inhal): 0.01; RCR(derm): 0.01
Proc 2	RCR(inhal): 0.161 ; RCR(derm): 0.124
Proc 3	RCR(inhal): 0.323 ; RCR(derm): 0.063
Proc 4	RCR(inhal): 0.645 ; RCR(derm): 0.125
Proc 5	RCR(inhal): 0.161; RCR(derm): 0.249
Proc 8a	RCR(inhal): 0.161 ; RCR(derm): 0.249
Proc 8b	RCR(inhal): 0.807 ; RCR(derm): 0.125
Proc 9	RCR(inhal): 0.161 ; RCR(derm): 0.624
Proc 14	RCR(inhal): 0.161 ; RCR(derm): 0.312
Proc 15	RCR(inhal): 0.323 ; RCR(derm): 0.031

## Number of the ES 2

Short title of the exposure scenario

### Distribution of substance

#### List of use descriptors

#### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

#### Environmental release categories [ERC]

ERC2: Formulation of preparations (mixtures)

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading, distribution and associated laboratory activities.

#### Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes an advanced standard of occupational Health and Safety Management System

### Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for  
ERC 2

#### Further specification

SpERC ESVOC 1.1b.v1 (ESVOC 3), release factors for (Sp)ERC were modified,

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

assessment tool used:, Chesar 2.3.

## Amounts used

Annual amount per site: 120000 to

Daily amount per site: 0.08 to

Fraction of Regional tonnage used locally: 0.002

## Frequency and duration of use

Covers use up to: 300 days

## Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

## Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

## Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0.01 %

Release fraction to wastewater from process: 0.001 %

Release fraction to soil from process: 0.001%

## Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Apply vapour recovery (Adsorption, ...). Assumed Efficiency: 90 %

## Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 88.9

## Number of the contributing scenario

2

## Contributing exposure scenario controlling worker exposure for PROC 1

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

3

## Contributing exposure scenario controlling worker exposure for PROC 2

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 3

### Further specification

Assessment tool used: Chesar 2.3

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8b

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)



# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 9

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic) PEC: 0.0003 mg/l; RCR: 0.01

Fresh Water (Sediment) PEC: 0.006 mg/kg dw; RCR: 0.01

Marine Water (Pelagic) PEC: 2.525E-5 mg/l; RCR: 0.01

Marine Water (Sediment) PEC: 5.06E-4 mg/kg dw; RCR: 0.01

Agricultural Soil PEC: 0.001 mg/kg dw; RCR: 0.016

Sewage Treatment Plant (Effluent) PEC: 4.459E-5 mg/l; RCR: 0.01

Man via environment – Inhalation Concentration in air: 0.009 mg/m<sup>3</sup>; RCR: 0.01

Man via environment – Oral Exposure via food consumption: 0.001 mg/kg bw/day; RCR: 0.01

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. EE(inhal): Estimated inhalative

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.194; EE(derm): 0.034
Proc 2	EE(inhal): 96.8; EE(derm): 1.37
Proc 3	EE(inhal): 193.6; EE(derm): 0.69
Proc 4	EE(inhal): 387.2; EE(derm): 1.372
Proc 8a	EE(inhal): 96.8; EE(derm): 2.742
Proc 8b	EE(inhal): 484; EE(derm): 1.371
Proc 9	EE(inhal): 96.8; EE(derm): 6.86
Proc 15	EE(inhal): 193.6; EE(derm): 0.34

## Risk characterisation

Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values. RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm).

Proc 1	RCR(inhal): 0.0003; RCR(derm): 0.003
Proc 2	RCR(inhal): 0.161; RCR(derm): 0.124
Proc 3	RCR(inhal): 0.323; RCR(derm): 0.063
Proc 4	RCR(inhal): 0.645; RCR(derm): 0.125
Proc 8a	RCR(inhal): 0.161; RCR(derm): 0.249
Proc 8b	RCR(inhal): 0.807; RCR(derm): 0.125
Proc 9	RCR(inhal): 0.161; RCR(derm): 0.624
Proc 15	RCR(inhal): 0.323; RCR(derm): 0.031

## Number of the ES 3

Short title of the exposure scenario

**Uses in coatings**

### List of use descriptors

#### Sector of uses [SU]

SU5: Manufacture of textiles, leather, fur

SU7: Printing and reproduction of recorded media

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

PROC15: Use as laboratory reagent

#### Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Covers the use in coatings (paints, inks, adhesives, etc) within closed or contained systems including incidental exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application activities and film formation) and equipment cleaning, maintenance and associated laboratory activities.

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

## Contributing Scenarios

**Number of the contributing scenario** 1  
**Contributing exposure scenario controlling environmental exposure for ERC 4**

### Further specification

SpERC ESVOC 4.3a.v1 (ESVOC 5), release factors for (Sp)ERC were modified, assessment tool used: Chesar 2.3.

### Amounts used

Daily amount per site: 16.66 to

Annual amount per site: 5000 to

Fraction of Regional tonnage used locally: 1

### Frequency and duration of use

Covers use up to: 300 days

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 9.8 %

Release fraction to wastewater from process: 0.02 %

Release fraction to soil from process: 0%

### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 90 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 99 %

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 88.9

Do not apply industrial sludge to natural soils

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 1**

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for**

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## PROC 2

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Number of the contributing scenario

4

### Contributing exposure scenario controlling worker exposure for PROC 3

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Number of the contributing scenario

5

### Contributing exposure scenario controlling worker exposure for PROC 4

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

### Number of the contributing scenario

6

### Contributing exposure scenario controlling worker exposure for PROC 5

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 7

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to hands and lower arms (1500 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

9

## Contributing exposure scenario controlling worker exposure for PROC 8b

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

## Number of the contributing scenario

10

## Contributing exposure scenario controlling worker exposure for PROC 10

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

11

## Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

12

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

Indoor and outdoor use

**Technical conditions and measures to control dispersion from source towards the worker**  
provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.019 mg/l; RCR: 0.105
Fresh Water (Sediment)	PEC: 0.378 mg/kg dw; RCR: 0.385
Marine Water (Pelagic)	PEC: 0.002 mg/l; RCR: 0.105
Marine Water (Sediment)	PEC: 0.038 mg/kg dw; RCR: 0.385
Agricultural Soil	PEC: 0.057 mg/kg dw; RCR: 0.632
Sewage Treatment Plant (Effluent)	PEC: 0.186 mg/l; RCR: 0.005
Man via environment – Oral	Exposure via food consumption: 0.004 mg/kg bw/day; RCR: 0.01

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.194; EE(derm): 0.034
Proc 2	EE(inhal): 96.8; EE(derm): 1.37
Proc 3	EE(inhal): 193.6; EE(derm): 0.69
Proc 4	EE(inhal): 387.2; EE(derm): 1.372
Proc 5	EE(inhal): 96.8; EE(derm): 2.742
Proc 7	EE(inhal): 242; EE(derm): 4.286
Proc 8a	EE(inhal): 96.8; EE(derm): 2.742
Proc 8b	EE(inhal): 484; EE(derm): 1.372
Proc 10	EE(inhal): 96.8; EE(derm): 5.486
Proc 13	EE(inhal): 96.8; EE(derm): 2.742
Proc 15	EE(inhal): 193.6; EE(derm): 0.34

### Risk characterisation

Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values. RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm).

Proc 1	RCR(inhal): 0.0003; RCR(derm): 0.003
Proc 2	RCR(inhal): 0.161; RCR(derm): 0.124
Proc 3	RCR(inhal): 0.323; RCR(derm): 0.063
Proc 4	RCR(inhal): 0.645; RCR(derm): 0.125
Proc 5	RCR(inhal): 0.161; RCR(derm): 0.249
Proc 7	RCR(inhal): 0.403; RCR(derm): 0.390
Proc 8a	RCR(inhal): 0.161; RCR(derm): 0.249
Proc 8b	RCR(inhal): 0.807; RCR(derm): 0.125
Proc 10	RCR(inhal): 0.161; RCR(derm): 0.499
Proc 13	RCR(inhal): 0.161; RCR(derm): 0.249
Proc 15	RCR(inhal): 0.323; RCR(derm): 0.031

## Number of the ES 4

Short title of the exposure scenario

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

## Uses in coatings

### List of use descriptors

#### Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC15: Use as laboratory reagent

PROC19: Hand-mixing with intimate contact and only PPE available

#### Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Covers the use in coatings (paints, inks, adhesives, etc) within closed or contained systems including incidental exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application activities and film formation) and equipment cleaning, maintenance and associated laboratory activities.

#### Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a basic standard of occupational Health and Safety Management System

## Contributing Scenarios

### Number of the contributing scenario

1

### Contributing exposure scenario controlling environmental exposure for ERC 8a

#### Further specification

SpERC ESVOC 8.3b.v1,

assessment tool used:, Chesar 2.3.

#### Amounts used

daily wide dispersive use: 0.00055 to/d

Fraction of EU tonnage used in region: 0.1

Fraction of Regional tonnage used locally: 0.0005

Amounts used (EU): 4000 to/a

#### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

#### Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

#### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from wide dispersive use (regional only): 98 %



# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

Release fraction to wastewater from wide dispersive use: 1 %  
Release fraction to soil from wide dispersive use (regional only): 1%

#### **Conditions and measures related to municipal sewage treatment plant**

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000  
The minimum grade of elimination in the sewage plant is (%): 88.9

#### **Conditions and measures related to external treatment of waste for disposal**

Dispose of waste product or used containers according to local regulations

**Number of the contributing scenario** 2  
**Contributing exposure scenario controlling worker exposure for PROC 1**

#### **Further specification**

Assessment tool used: Chesar 2.3

#### **Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

#### **Frequency and duration of use**

8 h (full shift)

#### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

#### **Other given operational conditions affecting workers exposure**

Indoor and outdoor use

#### **Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 2**

#### **Further specification**

Assessment tool used: Chesar 2.3

#### **Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

#### **Frequency and duration of use**

8 h (full shift)

#### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

#### **Other given operational conditions affecting workers exposure**

Indoor and outdoor use

#### **Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 4  
**Contributing exposure scenario controlling worker exposure for PROC 3**

#### **Further specification**

Assessment tool used: Chesar 2.3

#### **Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

#### **Frequency and duration of use**

8 h (full shift)

#### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

#### **Other given operational conditions affecting workers exposure**

Indoor and outdoor use

#### **Technical conditions and measures to control dispersion from source towards the worker**

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

provide a basic standard of general ventilation (1 to 3 air changes per hour).

**Number of the contributing scenario** 5  
**Contributing exposure scenario controlling worker exposure for PROC 4**

#### Further specification

Assessment tool used: Chesar 2.3

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

#### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

**Number of the contributing scenario** 6  
**Contributing exposure scenario controlling worker exposure for PROC 5**

#### Further specification

Assessment tool used: Chesar 2.3

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

#### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

#### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

**Number of the contributing scenario** 7  
**Contributing exposure scenario controlling worker exposure for PROC 8a**

#### Further specification

Assessment tool used: Chesar 2.3

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

#### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

#### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

**Number of the contributing scenario** 8  
**Contributing exposure scenario controlling worker exposure for PROC 8b**

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

**Number of the contributing scenario 9**

**Contributing exposure scenario controlling worker exposure for PROC 10**

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. provide a basic standard of general ventilation (1 to 3 air changes per hour). Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Number of the contributing scenario 10**

**Contributing exposure scenario controlling worker exposure for PROC 11**

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 25 %

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to hands and lower arms (1500 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear respiratory protection (Efficiency: 95 %).

**Number of the contributing scenario 11**

**Contributing exposure scenario controlling worker exposure for PROC 11**

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to hands and lower arms (1500 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear respiratory protection (Efficiency: 90 %).

### Number of the contributing scenario

12

### Contributing exposure scenario controlling worker exposure for PROC 11

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

### Human factors not influenced by risk management

Area potentially exposed: corresponds to hands and lower arms (1500 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear respiratory protection (Efficiency: 95 %).

### Number of the contributing scenario

13

### Contributing exposure scenario controlling worker exposure for PROC 13

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 25 %

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

### Number of the contributing scenario

14

### Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

15

## Contributing exposure scenario controlling worker exposure for PROC 19

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 1980 cm<sup>2</sup>

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear respiratory protection (Efficiency: 95 %).

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.0003 mg/l; RCR: 0.01
Fresh Water (Sediment)	PEC: 0.006 mg/kg dw; RCR: 0.01
Marine Water (Pelagic)	PEC: 2.786E-5 mg/l; RCR: 0.01
Marine Water (Sediment)	PEC: 0.0006 mg/kg dw; RCR: 0.01
Agricultural Soil	PEC: 0.0001 mg/kg dw; RCR: 0.01
Sewage Treatment Plant (Effluent)	PEC: 0.0003 mg/l; RCR: 0.01
Man via environment – Inhalation	Concentration in air: 1.051E-4 mg/m <sup>3</sup> ; RCR: 0.01
Man via environment – Oral	Exposure via food consumption: 1.734E-5 mg/kg bw/day; RCR: 0.01

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.194; EE(derm): 0.034
Proc 2	EE(inhal): 387.2; EE(derm): 1.37
Proc 3	EE(inhal): 484; EE(derm): 0.69
Proc 4	EE(inhal): 193.6; EE(derm): 6.86
Proc 5	EE(inhal): 387.2; EE(derm): 2.742
Proc 8a	EE(inhal): 387.2; EE(derm): 2.742
Proc 8b	EE(inhal): 96.8; EE(derm): 2.742
Proc 10	EE(inhal): 387.2; EE(derm): 2.743
Proc 11	EE(inhal): 203.3; EE(derm): 6.428 - Contributing Scenarios 10
	EE(inhal): 193.6; EE(derm): 6.428 - Contributing Scenarios 11
	EE(inhal): 290.4; EE(derm): 3.857 - Contributing Scenarios 12

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

Proc 13	EE(inhal): 232.3; EE(derm): 1.645
Proc 15	EE(inhal): 193.6 ; EE(derm): 0.34
Proc 19	EE(inhal): 135.5; EE(derm): 8.486

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0003; RCR(derm): 0.003
Proc 2	RCR(inhal): 0.645; RCR(derm): 0.124
Proc 3	RCR(inhal): 0.807; RCR(derm): 0.063
Proc 4	RCR(inhal): 0.323; RCR(derm): 0.624
Proc 5	RCR(inhal): 0.645; RCR(derm): 0.249
Proc 8a	RCR(inhal): 0.645; RCR(derm): 0.249
Proc 8b	RCR(inhal): 0.161; RCR(derm): 0.249
Proc 10	RCR(inhal): 0.645; RCR(derm): 0.249
Proc 11	RCR(inhal): 0.339; RCR(derm): 0.584 - Contributing Scenarios 10 RCR(inhal): 0.323; RCR(derm): 0.584 - Contributing Scenarios 11 RCR(inhal): 0.484; RCR(derm): 0.351 - Contributing Scenarios 12
Proc 13	RCR(inhal): 0.387; RCR(derm): 0.149
Proc 15	RCR(inhal): 0.323; RCR(derm): 0.031
Proc 19	RCR(inhal): 0.226; RCR(derm): 0.772

## Number of the ES 5

Short title of the exposure scenario

**Use in Cleaning Products**

### List of use descriptors

#### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

SU8: Manufacture of bulk, large scale chemicals (including petroleum products)

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

#### Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

containers. exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

## Contributing Scenarios

<b>Number of the contributing scenario</b>	<b>1</b>
<b>Contributing exposure scenario controlling environmental exposure for ERC 4</b>	

### Further specification

SpERC ESVOC 4.4a.v1 (ESVOC 8), release factors for (Sp)ERC were modified, assessment tool used: Chesar 2.3.

### Amounts used

Daily amount per site: 5 to

Annual amount per site: 100 to

Fraction of Regional tonnage used locally: 1

### Frequency and duration of use

Covers use up to: 20 days

### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 50%

Release fraction to wastewater from process: 0.01 %

Release fraction to soil from process: 0%

### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 50 %

### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 88.9

<b>Number of the contributing scenario</b>	<b>2</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 1</b>	

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

<b>Number of the contributing scenario</b>	<b>3</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 2</b>	

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 3

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 7

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to hands and lower arms (1500 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor use



# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

## **Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

## **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Number of the contributing scenario** 7

## **Contributing exposure scenario controlling worker exposure for PROC 8a**

### **Further specification**

Assessment tool used: Chesar 2.3

### **Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### **Frequency and duration of use**

8 h (full shift)

### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## **Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear suitable gloves tested to EN374.

**Number of the contributing scenario** 8

## **Contributing exposure scenario controlling worker exposure for PROC 8b**

### **Further specification**

Assessment tool used: Chesar 2.3

### **Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### **Frequency and duration of use**

8 h (full shift)

### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### **Other given operational conditions affecting workers exposure**

Indoor and outdoor use

## **Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## **Conditions and measures related to personal protection, hygiene and health evaluation**

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Number of the contributing scenario** 9

## **Contributing exposure scenario controlling worker exposure for PROC 10**

### **Further specification**

Assessment tool used: Chesar 2.3

### **Product characteristics**

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### **Frequency and duration of use**

8 h (full shift)

### **Human factors not influenced by risk management**

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## **Technical conditions and measures to control dispersion from source towards the worker**

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

### Number of the contributing scenario

10

### Contributing exposure scenario controlling worker exposure for PROC 13

#### Further specification

Assessment tool used: Chesar 2.3

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

#### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

#### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.003 mg/l; RCR: 0.017
Fresh Water (Sediment)	PEC: 0.061 mg/kg dw; RCR: 0.062
Marine Water (Pelagic)	PEC: 0.0003 mg/l; RCR: 0.017
Marine Water (Sediment)	PEC: 0.006 mg/kg dw; RCR: 0.062
Agricultural Soil	PEC: 0.016 mg/kg dw; RCR: 0.179
Sewage Treatment Plant (Effluent)	PEC: 0.028 mg/l; RCR: 0.01
Man via environment – Inhalation	Concentration in air: 0.038 mg/m <sup>3</sup> ; RCR: < 0.01
Man via environment – Oral	Exposure via food consumption: 4.391E-4 mg/kg bw/day; RCR: 0.01

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.194; EE(derm): 0.034
Proc 2	EE(inhal): 96.8; EE(derm): 1.37
Proc 3	EE(inhal): 193.6; EE(derm): 0.69
Proc 4	EE(inhal): 387.2; EE(derm): 1.372
Proc 7	EE(inhal): 242; EE(derm): 4.286
Proc 8a	EE(inhal): 96.8; EE(derm): 2.742
Proc 8b	EE(inhal): 484; EE(derm): 1.372
Proc 10	EE(inhal): 96.8; EE(derm): 5.486
Proc 13	EE(inhal): 96.8; EE(derm): 2.742

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0003; RCR(derm): 0.003
--------	--------------------------------------

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

Proc 2	RCR(inhal): 0.161; RCR(derm): 0.124
Proc 3	RCR(inhal): 0.323; RCR(derm): 0.063
Proc 4	RCR(inhal): 0.645; RCR(derm): 0.125
Proc 7	RCR(inhal): 0.403; RCR(derm): 0.390
Proc 8a	RCR(inhal): 0.161; RCR(derm): 0.249
Proc 8b	RCR(inhal): 0.807; RCR(derm): 0.125
Proc 10	RCR(inhal): 0.161; RCR(derm): 0.499
Proc 13	RCR(inhal): 0.161; RCR(derm): 0.249

## Number of the ES 6

Short title of the exposure scenario

### Use in Cleaning Products

#### List of use descriptors

#### Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

#### Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

#### Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

#### Product characteristics

Refer to attached safety data sheets

#### Processes and activities covered by the exposure scenario

Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand).

#### Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a basic standard of occupational Health and Safety Management System

#### Contributing Scenarios

#### Number of the contributing scenario

1

#### Contributing exposure scenario controlling environmental exposure for ERC 8a

#### Further specification

SpERC ESVOC 8.4b.v1 (ESVOC 9),  
assessment tool used: Chesar 2.3.

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Amounts used

daily wide dispersive use: 0.0003 to/d  
Fraction of EU tonnage used in region: 0.1  
Fraction of Regional tonnage used locally: 0.0005  
Amounts used (EU): 2000 to/a

## Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

## Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

## Technical conditions and measures at process level (source) to prevent release

Release fraction to air from wide dispersive use (regional only): 2 %  
Release fraction to wastewater from wide dispersive use: 0.0001 %  
Release fraction to soil from wide dispersive use (regional only): 0%

## Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000  
The minimum grade of elimination in the sewage plant is (%): 88.9

## Number of the contributing scenario

2

## Contributing exposure scenario controlling worker exposure for PROC 1, PROC 3

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

3

## Contributing exposure scenario controlling worker exposure for PROC 2

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP  
Covers percentage substance in the product up to 100 % (unless stated differently)

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

4

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 5 %

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

5

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 25 %

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

## Number of the contributing scenario

6

## Contributing exposure scenario controlling worker exposure for PROC 4

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

## Number of the contributing scenario

7

## Contributing exposure scenario controlling worker exposure for PROC 8a

## Further specification

Assessment tool used: Chesar 2.3

## Product characteristics

Covers percentage substance in the product up to 5 %

Liquid, vapour pressure 0,5 - 10 kPa at STP

## Frequency and duration of use

8 h (full shift)

## Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

## Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Number of the contributing scenario

8

## Contributing exposure scenario controlling worker exposure for

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## PROC 8a

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

### Number of the contributing scenario

9

### Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 5 %

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Number of the contributing scenario

10

### Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 25 %

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

### Number of the contributing scenario

11

### Contributing exposure scenario controlling worker exposure for PROC 8b

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

### Number of the contributing scenario

12

### Contributing exposure scenario controlling worker exposure for PROC 10

## Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 5 %

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

### Number of the contributing scenario

13

### Contributing exposure scenario controlling worker exposure for PROC 10

## Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### Number of the contributing scenario

14

### Contributing exposure scenario controlling worker exposure for PROC 11

## Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 5 %

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

Area potentially exposed: corresponds to hands and lower arms (1500 cm<sup>2</sup>)

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.

### Number of the contributing scenario

15

### Contributing exposure scenario controlling worker exposure for PROC 13

#### Further specification

Assessment tool used: Chesar 2.3

#### Product characteristics

Covers percentage substance in the product up to 25 %

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

### Number of the contributing scenario

16

### Contributing exposure scenario controlling worker exposure for PROC 13

#### Further specification

Assessment tool used: Chesar 2.3

#### Product characteristics

Covers percentage substance in the product up to 5 %

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm<sup>2</sup>)

#### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.0003 mg/l; RCR: 0.01
Fresh Water (Sediment)	PEC: 0.005 mg/kg dw; RCR: 0.01
Marine Water (Pelagic)	PEC: 0.00002 mg/l; RCR: 0.01
Marine Water (Sediment)	PEC: 0.0005 mg/kg dw; RCR: 0.01
Agricultural Soil	PEC: 0.00004 mg/kg dw; RCR: 0.01
Sewage Treatment Plant (Effluent)	PEC: 1.527E-8 mg/l; RCR: 0.01
Man via environment – Inhalation	Concentration in air: 1.05E-4 mg/m <sup>3</sup> ; RCR: 0.01
Man via environment – Oral	Exposure via food consumption: 1.556E-5 mg/kg bw/day; RCR: 0.01

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm):



# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 1	EE(inhal): 0.194; EE(derm): 0.034
Proc 2	EE(inhal): 387.2; EE(derm): 1.37
Proc 3	EE(inhal): 484; EE(derm): 0.69
Proc 4	EE(inhal): 193.6; EE(derm): 1.372 - Contributing Scenarios 4
	EE(inhal): 406.6; EE(derm): 0.823 - Contributing Scenarios 5
	EE(inhal): 193.6; EE(derm): 6.86 - Contributing Scenarios 6
Proc 8a	EE(inhal): 387.2; EE(derm): 2.742 - Contributing Scenarios 7
	EE(inhal): 387.2; EE(derm): 2.742 - Contributing Scenarios 8
Proc 8b	EE(inhal): 193.6; EE(derm): 2.742 - Contributing Scenarios 9
	EE(inhal): 406.6 ; EE(derm): 1.645 - Contributing Scenarios 10
	EE(inhal): 96.8 ; EE(derm): 2.742 - Contributing Scenarios 11
Proc 10	EE(inhal): 387.2; EE(derm): 1.097 - Contributing Scenarios 12
	EE(inhal): 387.2; EE(derm): 2.743 - Contributing Scenarios 13
Proc 11	EE(inhal): 387.2 ; EE(derm): 2.143
Proc 13	EE(inhal): 232.3 ; EE(derm): 1.645 - Contributing Scenarios 15
	EE(inhal): 387.2 ; EE(derm): 2.742 - Contributing Scenarios 16

## Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 1	RCR(inhal): 0.0003; RCR(derm): 0.003
Proc 2	RCR(inhal): 0.645; RCR(derm): 0.124
Proc 3	RCR(inhal): 0.807; RCR(derm): 0.063
Proc 4	RCR(inhal): 0.323; RCR(derm): 0.125 - Contributing Scenarios 4
	RCR(inhal): 0.678; RCR(derm): 0.075 - Contributing Scenarios 5
	RCR(inhal): 0.323; RCR(derm): 0.624 - Contributing Scenarios 6
Proc 8a	RCR(inhal): 0.645; RCR(derm): 0.249 - Contributing Scenarios 7
	RCR(inhal): 0.645; RCR(derm): 0.249 - Contributing Scenarios 8
Proc 8b	RCR(inhal): 0.323; RCR(derm): 0.249 - Contributing Scenarios 9
	RCR(inhal): 0.678; RCR(derm): 0.149 - Contributing Scenarios 10
	RCR(inhal): 0.161; RCR(derm): 0.249 - Contributing Scenarios 11
Proc 10	RCR(inhal): 0.645; RCR(derm): 0.100 - Contributing Scenarios 12
	RCR(inhal): 0.645; RCR(derm): 0.249 - Contributing Scenarios 13
Proc 11	RCR(inhal): 0.645; RCR(derm): 0.195
Proc 13	RCR(inhal): 0.387; RCR(derm): 0.149 - Contributing Scenarios 15
	RCR(inhal): 0.645; RCR(derm): 0.249 - Contributing Scenarios 16

## Number of the ES 7

Short title of the exposure scenario

## Use in laboratories

## List of use descriptors

### Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

### Process categories [PROC]

PROC10: Roller application or brushing

PROC15: Use as laboratory reagent

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

## Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Use of the substance within laboratory settings, including material transfers and equipment cleaning

## Further explanations

Industrial use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

## Contributing Scenarios

<b>Number of the contributing scenario</b>	<b>1</b>
<b>Contributing exposure scenario controlling environmental exposure for ERC 4</b>	

### Further specification

assessment tool used: Chesar 2.3.

#### Amounts used

Daily amount per site: 0.05 to

Annual amount per site: 1 to

Fraction of Regional tonnage used locally: 1

#### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

#### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 100 %

Release fraction to wastewater from process: 10 %

Release fraction to soil from process: 5%

#### Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 90 %

#### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 88.9

Do not apply industrial sludge to natural soils

<b>Number of the contributing scenario</b>	<b>2</b>
<b>Contributing exposure scenario controlling worker exposure for PROC 10</b>	

### Further specification

Assessment tool used: Chesar 2.3

#### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

#### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

#### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

<b>Number of the contributing scenario</b>	<b>3</b>
--	----------

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

Version / Revision 9

## Contributing exposure scenario controlling worker exposure for PROC 15

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.028 mg/l; RCR: 0.156
Fresh Water (Sediment)	PEC: 0.564 mg/kg dw; RCR: 0.575
Marine Water (Pelagic)	PEC: 0.003 mg/l; RCR: 0.156
Marine Water (Sediment)	PEC: 0.056 mg/kg dw; RCR: 0.574
Agricultural Soil	PEC: 0.0002 mg/kg dw; RCR: 0.002
Sewage Treatment Plant (Effluent)	PEC: 0.279 mg/l; RCR: 0.008
Man via environment – Inhalation	Concentration in air: 8.666E-4 mg/m <sup>3</sup> ; RCR: 0.01
Man via environment – Oral	Exposure via food consumption: 1.036E-4 mg/kg bw/day; RCR: 0.01

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 10	EE(inhal):	96.8; EE(derm):	5.486
Proc 15	EE(inhal):	193.6; EE(derm):	0.34

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 10	RCR(inhal):	0.161; RCR(derm):	0.499
Proc 15	RCR(inhal):	0.323; RCR(derm):	0.031

## Number of the ES 8

Short title of the exposure scenario

## Use in laboratories

## List of use descriptors

## Sector of uses [SU]

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

## Process categories [PROC]

PROC10: Roller application or brushing

PROC15: Use as laboratory reagent

## Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

## Product characteristics

Refer to attached safety data sheets

## Processes and activities covered by the exposure scenario

Use of small quantities within laboratory settings, including material transfers and equipment cleaning

## Further explanations

Professional use

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Assumes a basic standard of occupational Health and Safety Management System

## Contributing Scenarios

### Number of the contributing scenario

1

### Contributing exposure scenario controlling environmental exposure for ERC 8a

#### Further specification

SpERC ESVOC 8.17.v1 (ESVOC 39),

assessment tool used: Chesar 2.3.

#### Amounts used

daily wide dispersive use: 0.0000001 to/d

Fraction of EU tonnage used in region: 0.1

Fraction of Regional tonnage used locally: 0.0005

Amounts used (EU): 1 to/a

#### Environment factors not influenced by risk management

River flow rate: 18000 m<sup>3</sup>/d Local freshwater dilution factor: 10 Local marine water dilution factor: 100

#### Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

#### Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 50 %

Release fraction to wastewater from process: 50 %

Release fraction to soil from process: 0%

#### Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m<sup>3</sup>/d): 2000

The minimum grade of elimination in the sewage plant is (%): 88.9

### Number of the contributing scenario

2

### Contributing exposure scenario controlling worker exposure for PROC 10

#### Further specification

Assessment tool used: Chesar 2.3

#### Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid, vapour pressure 0,5 - 10 kPa at STP

#### Frequency and duration of use

8 h (full shift)

#### Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm<sup>2</sup>)

#### Technical conditions and measures to control dispersion from source towards the worker

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, respiratory protection (efficiency 90 %) must be used.

### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.

**Number of the contributing scenario** 3  
**Contributing exposure scenario controlling worker exposure for PROC 15**

### Further specification

Assessment tool used: Chesar 2.3

### Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

### Frequency and duration of use

8 h (full shift)

### Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm<sup>2</sup>)

### Other given operational conditions affecting workers exposure

Indoor and outdoor use

### Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

## Exposure estimation and reference to its source

### Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

Fresh Water (Pelagic)	PEC: 0.00027 mg/l; RCR: 0.01
Fresh Water (Sediment)	PEC: 0.005 mg/kg dw; RCR: 0.01
Marine Water (Pelagic)	PEC: 0.00002 mg/l; RCR: 0.01
Marine Water (Sediment)	PEC: 0.0005 mg/kg dw; RCR: 0.01
Agricultural Soil	PEC: 0.00004 mg/kg dw; RCR: 0.01
Sewage Treatment Plant (Effluent)	PEC: 3.818E-6 mg/l; RCR: 0.01
Man via environment – Inhalation	Concentration in air: 1.05E-4 mg/m <sup>3</sup> ; RCR: 0.01
Man via environment – Oral	Exposure via food consumption: 1.558E-5 mg/kg bw/day; RCR: 0.01

### Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m<sup>3</sup>]; EE(derm): Estimated dermal long-term exposure [mg/kg b.w./d]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios. The RMMs described above suffice to control risks for both local and systemic effects.

Proc 10	EE(inhal):	271 ; EE(derm):	5.486
Proc 15	EE(inhal):	193.6 ; EE(derm):	0.34

### Risk characterisation

RCR(inhal): inhalative risk characterisation ratio; RCR(derm): dermal risk characterisation ratio; total RCR= RCR(inhal) +RCR(derm). Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

Proc 10	RCR(inhal):	0.452; RCR(derm):	0.499
Proc 15	RCR(inhal):	0.323; RCR(derm):	0.031

## Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

# SAFETY DATA SHEET

according to REACH Regulation (EC) No. 1907/2006, as amended by UK REACH Regulations SI 2019/758



**n-Butyl acetate**  
**10430**

**Version / Revision** 9

---

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as  $M(\text{site})$  [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

For specific information regarding the SPERC used please refer to the ESIG webpage  
<https://www.esig.org/reach-ges/environment/>

**associated uses:**

Should consumer uses be associated with this exposure scenario, please contact OQ for further details  
Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe