

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2
Supersedes Version 1.02***

Revision Date 04-Sep-2020
Issuing date 04-Sep-2020

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Identification of the
substance/preparation

Trimethylolpropane molten

CAS-No 77-99-6
EC No. 201-074-9
Registration number (REACH) 01-2119486799-10***

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Intermediate
Polymerization***
Uses advised against None

1.3. Details of the supplier of the safety data sheet

Company/Undertaking **OQ Chemicals GmbH**
Identification Rheinpromenade 4A
D-40789 Monheim
Germany

Product Information Product Stewardship
FAX: +49 (0)208 693 2053
email: sc.psq@oq.com

1.4. Emergency telephone number

Emergency telephone number +44 (0) 1235 239 670 (UK)
available 24/7***

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

This substance is classified based on Directive 1272/2008/EC and its amendments (CLP Regulation)***

Reproductive toxicity Category 2, H361***

Additional information

For full text of Hazard- and EU Hazard-statements see SECTION 16.***

2.2. Label elements

Labelling according to Regulation 1272/2008/EC and its amendments (CLP Regulation).***

Hazard pictograms ***

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2



Signal word

Warning***

Hazard statements

H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.***

Precautionary statements

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P308 + P313: IF exposed or concerned: Get medical advice/ attention.
P405: Store locked up.
P501: Dispose of contents/container in accordance with local regulation.***

2.3. Other hazards

Caution Hot!

Contact with product at elevated temperatures can result in thermal burns

PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition / information on ingredients

3.1. Substances

Component	CAS-No	REACH-No	1272/2008/EC	Concentration (%)
Trimethylolpropane (TMP)	77-99-6	01-2119486799-10** *	Repr. 2; H361fd***	> 98,0

For full text of Hazard- and EU Hazard-statements see SECTION 16.***

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Keep at rest. Aerate with fresh air. When symptoms persist or in all cases of doubt seek medical advice.

Skin

Wash off immediately with soap and plenty of water. When symptoms persist or in all cases of doubt seek medical advice.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

Ingestion

Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Main symptoms

cough.

Special hazard

Lung irritation, Contact with product at elevated temperatures can result in thermal burns.

4.3. Indication of any immediate medical attention and special treatment needed

General advice

Remove contaminated, soaked clothing immediately and dispose of safely. First aider needs to protect himself.

Treat symptomatically. If ingested, irrigate the stomach using activated charcoal.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

foam, dry chemical, carbon dioxide (CO₂), water spray

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Under conditions giving incomplete combustion, hazardous gases produced may consist of:

carbon monoxide (CO)

carbon dioxide (CO₂)

Combustion gases of organic materials must in principle be graded as inhalation poisons

Vapours are heavier than air and may spread along floors

5.3. Advice for firefighters

Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Keep people away from and upwind of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: For personal protective equipment see section 8. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.

For emergency responders: Personal protection see section 8.***



Trimethylolpropane molten
10700

Version / Revision 2

6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

6.3. Methods and material for containment and cleaning up

Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

Methods for cleaning up

Use mechanical handling equipment. Keep in suitable, closed containers for disposal. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

6.4. Reference to other sections

For personal protective equipment see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Further info may be available in the appropriate Exposure scenarios in the annex to this SDS.***

Advice on safe handling

Do not handle hot or molten material without appropriate protective equipment. Do not exceed recommended process temperatures to minimize release of decomposition products. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms. Handle product only in closed system or provide appropriate exhaust ventilation at machinery.***

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Advice on the protection of the environment

See Section 8: Environmental exposure controls.

Incompatible products

strong oxidizing agents

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material.

Technical measures/Storage conditions

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care. Keep at temperatures between 76 and 104 °C (170 and 220 °F).

Temperature class

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

T2

7.3. Specific end use(s)

Intermediate

Polymerization***

For specific end use information see the annex of this safety data sheet***

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Exposure limits European Union

No exposure limits established

Exposure limits UK

No exposure limits established.

DNEL & PNEC

Trimethylolpropane (TMP), CAS: 77-99-6

Workers

DN(M)EL - long-term exposure - systemic effects - Inhalation	3,3*** mg/m ³ ***
DN(M)EL - acute / short-term exposure - systemic effects - Inhalation	No hazard identified***
DN(M)EL - long-term exposure - local effects - Inhalation	No hazard identified***
DN(M)EL - acute / short-term exposure - local effects - Inhalation	No hazard identified***
DN(M)EL - long-term exposure - systemic effects - Dermal	0,94*** mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Dermal	No hazard identified***
DN(M)EL - long-term exposure - local effects - Dermal	No hazard identified***
DN(M)EL - acute / short-term exposure - local effects - Dermal	No hazard identified***
DN(M)EL - local effects - eyes	No hazard identified***

General population

DN(M)EL - long-term exposure - systemic effects - Inhalation	0,58*** mg/m ³ ***
DN(M)EL - acute / short-term exposure - systemic effects - Inhalation	No hazard identified***
DN(M)EL - long-term exposure - local effects - Inhalation	No hazard identified***
DN(M)EL - acute / short-term exposure - local effects - Inhalation	No hazard identified***
DN(M)EL - long-term exposure - systemic effects - Dermal	0,34*** mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Dermal	No hazard identified***
DN(M)EL - long-term exposure - local effects - Dermal	No hazard identified***
DN(M)EL - acute / short-term exposure - local effects - Dermal	No hazard identified***
DN(M)EL - long-term exposure - systemic effects - Oral	0,34*** mg/kg bw/day
DN(M)EL - acute / short-term exposure - systemic effects - Oral	No hazard identified***
DN(M)EL - local effects - eyes	No hazard identified***

Environment

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

PNEC aqua - freshwater	No hazard identified***
PNEC aqua - marine water	No hazard identified***
PNEC STP	No hazard identified***
PNEC sediment - marine water	No hazard identified***
PNEC soil	No hazard identified***
Secondary poisoning	No potential for bioaccumulation***

8.2. Exposure controls

Special adaptations (REACH)

Not applicable.***

Appropriate Engineering controls

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

Personal protective equipment

General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe dust or mist. Ensure that eyewash stations and safety showers are close to the workstation location.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Equipment should conform to EN 166

Hand protection

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

Suitable material	Heat resistant gloves
--------------------------	-----------------------

Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

Respiratory protection

Respirator with A filter. Full mask with above mentioned filter according to producers using requirements or self-contained breathing apparatus. Equipment should conform to EN 136 or EN 140 and EN 143.***

Thermal Hazard

Heat only in areas with appropriate exhaust ventilation. When handling hot material, use heat resistant gloves.***

Environmental exposure controls

Use product only in closed system. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. Observe the exposure limits, clean exhaust air if needed. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

leakage into the atmosphere, or of entry into waterways, soil or drains.***

Additional advice

Further details on substance data can be found in the registration dossier under the following link:
<http://echa.europa.eu/information-on-chemicals/registered-substances>.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Hot viscous liquid				
Colour	white				
Odour	light alcoholic				
Odour threshold	No data available				
pH	5,6 @ 25 °C (77 °F)				
Melting point/range	58 °C				
Boiling point/range	304 °C @ 1013 hPa				
Flash point	149 - 180 °C				
Method	DIN 51755				
Evaporation rate	No data available				
Flammability (solid, gas)	Does not apply, the substance is a liquid				
Lower explosion limit	2 Vol %				
Upper explosion limit	11,8 Vol %				
Vapour pressure	***				
Values [hPa]	Values [kPa]	Values [atm]	@ °C	@ °F	Method
< 0,001	< 0,0001	< 0,0001	20	68	
Vapour density	4,63 (Air = 1) @ 20 °C (68 °F)				
Relative density	***				
Values	@ °C	@ °F	Method		
1,084 - 1,09	20	68			
Solubility	100 - 1000 g/l @ 20 °C, in water***				
log Pow	-0,47 (measured)				
Autoignition temperature	~ 375 °C				
Method	DIN 51794				
Decomposition temperature	No data available				
Viscosity	No data available				
Explosive properties	Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties				
Oxidizing properties	Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties				

9.2. Other information

Molecular weight 134,17
Molecular formula C6 H14 O3
hygroscopic.

SECTION 10: Stability and Reactivity

10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

any text book on organic chemistry.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerisation does not occur.***

10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.

10.5. Incompatible materials

strong oxidizing agents.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure Inhalation, Eye contact, Skin contact, Ingestion***

Acute toxicity				
Trimethylolpropane (TMP) (77-99-6)				
Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	~ 14700 mg/kg	rat, male	OECD 401
Dermal	LD50	> 10000 mg/kg	rabbit	OECD 402
Inhalative	LC50	> 0,85 mg/l (4h)	rat, male	

Trimethylolpropane (TMP), CAS: 77-99-6

Assessment

Based on available data, the classification criteria are not met for:

Acute oral toxicity

Acute dermal toxicity

Acute inhalation toxicity

STOT SE***

Irritation and corrosion				
Trimethylolpropane (TMP) (77-99-6)				
Target Organ Effects	Species	Result	Method	
Skin	rabbit	No skin irritation		
Eyes	rabbit	No eye irritation		

Trimethylolpropane (TMP), CAS: 77-99-6

Assessment

Based on available data, the classification criteria are not met for:

skin irritation/corrosion

eye irritation/corrosion

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

For respiratory irritation, no data are available***

Sensitization				
Trimethylolpropane (TMP) (77-99-6)				
Target Organ Effects	Species	Evaluation	Method	
Skin	mouse	not sensitizing	OECD 429	

Trimethylolpropane (TMP), CAS: 77-99-6

Assessment

Based on available data, the classification criteria are not met for:

Skin sensitization

For respiratory sensitization, no data are available***

Subacute, subchronic and prolonged toxicity				
Trimethylolpropane (TMP) (77-99-6)				
Type	Dose	Species	Method	
Subchronic toxicity	NOAEL: ~ 67 mg/kg/d (90d)	rat, male/female		Oral

Trimethylolpropane (TMP), CAS: 77-99-6

Assessment

Based on available data, the classification criteria are not met for:

STOT RE***

Carcinogenicity, Mutagenicity, Reproductive toxicity					
Trimethylolpropane (TMP) (77-99-6)					
Type	Dose	Species	Evaluation	Method	
Mutagenicity		Salmonella typhimurium	negative	OECD 471 (Ames)	In vitro study
Mutagenicity		CHL	negative	OECD 473 (Chromosomal Aberration)	In vitro study
Mutagenicity		V79 cells, Chinese hamster	negative	OECD 476 (Mammalian Gene Mutation)	In vitro study
Reproductive toxicity	NOAEL 800 mg/kg/d	rat, parental		OECD 422, Oral	in vivo***
Reproductive toxicity	NOAEL 800 mg/kg/d	rat, 1. Generation, male/female		OECD 422, Oral	in vivo***
Reproductive toxicity***	NOAEL: 740 ppm***	rat rat, parental***		OECD 443 Oral***	in vivo***
Reproductive toxicity***	NOAEL: 2200 ppm***	rat, 1. Generation, male/female***		OECD 443 Oral***	in vivo***
Developmental Toxicity***	NOAEL 100 mg/kg/d***	rat***		OECD 414, Oral***	in vivo***
Developmental Toxicity***	NOAEL 100 mg/kg/d***	rabbit***		OECD 414, Oral***	in vivo***

Trimethylolpropane (TMP), CAS: 77-99-6

CMR Classification

The available data on CMR properties are summarized in the table above. They do not indicate a classification

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

into categories 1A or 1B

The substance has been classified as:

Repr. 2***

Evaluation

In vitro tests did not show mutagenic effects

In the absence of specific alerts no cancer testing is required

Suspected of damaging fertility or the unborn child***

Trimethylolpropane (TMP), CAS: 77-99-6

Main symptoms

cough.

Target Organ Systemic Toxicant - Single exposure

Based on available data, the classification criteria are not met for:

STOT SE***

Target Organ Systemic Toxicant - Repeated exposure

Based on available data, the classification criteria are not met for:

STOT RE***

Aspiration toxicity

no data available***

Note

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link:

<http://echa.europa.eu/information-on-chemicals/registered-substances>.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity

Trimethylolpropane (TMP) (77-99-6)

Species	Exposure time	Dose	Method
Daphnia magna (Water flea)	48h	EC50: 13000 mg/l	
Alburnus alburnus	96h	LC50: > 1000 mg/l	DEV L8
Pseudokirchneriella subcapitata	72h	EC50: > 1000 mg/l	
Activated sludge (domestic)	3 h	EC50: > 1000 mg/l	DIN 38412, part 11***

Long term toxicity

Trimethylolpropane (TMP) (77-99-6)

Type	Species	Dose	Method
Mortality	Daphnia magna (Water flea)	NOEC: > 1000 mg/l (21d)	

12.2. Persistence and degradability

Trimethylolpropane (TMP), CAS: 77-99-6

Biodegradation

6 % (28 d), activated sludge, industrial, non-adapted, OECD 301 E, Not readily biodegradable,

100 % (28*** d), activated sludge, OECD 302 B (Zahn-Wellens Test), Inherently biodegradable.***

Abiotic Degradation

Trimethylolpropane (TMP) (77-99-6)

Type	Result	Method
Hydrolysis***	Half-life (DT50): > 356 d @	OECD 111***

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

	25°C***	
Photolysis***	Half-life (DT50): 1,2 days***	calculated***

12.3. Bioaccumulative potential

Trimethylolpropane (TMP) (77-99-6)		
Type	Result	Method
log Pow***	-0,47***	measured***
log BCF***	< 2***	calculated, OECD 305 C***

12.4. Mobility in soil

Trimethylolpropane (TMP) (77-99-6)		
Type	Result	Method
Surface tension***	71 mN/m @ 20 °C (68 °F)***	measured***
Adsorption/Desorption***	Koc: 1,5***	calculated***
Distribution to environmental compartments***	Air: 0,32 Soil: 59,7 Water: 39,9 Sediment: 0,07***	Calculation according Mackay, Level III***

12.5. Results of PBT and vPvB assessment

Trimethylolpropane (TMP), CAS: 77-99-6

PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

12.6. Other adverse effects

Trimethylolpropane (TMP), CAS: 77-99-6

No data available***

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product Information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Hazardous waste according to European Waste Catalogue (EWC)***

Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

ADR/RID

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

14.1. UN number *** UN 3257
14.2. UN proper shipping name *** Elevated temperature liquid, n.o.s.
(Trimethylolpropane)
14.3. Transport hazard class(es) *** 9
14.4. Packing group *** III
14.5. Environmental hazards no***
14.6. Special precautions for user ***
ADR Tunnel restriction code (D)
Classification Code M9
Hazard Number 99

ADN

ADN: Container and Tanker

14.1. UN number *** UN 3257
14.2. UN proper shipping name *** Elevated temperature liquid, n.o.s.
(Trimethylolpropane)
14.3. Transport hazard class(es) *** 9
14.4. Packing group *** III
14.5. Environmental hazards no***
14.6. Special precautions for user ***
Classification Code M9
Hazard Number 99

ICAO-TI / IATA-DGR

forbidden

IMDG

14.1. UN number *** UN 3257
14.2. UN proper shipping name *** Elevated temperature liquid, n.o.s.
(Trimethylolpropane)***
14.3. Transport hazard class(es) *** 9
14.4. Packing group *** III
14.5. Environmental hazards no***
14.6. Special precautions for user ***
EmS F-A, S-P
14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code not applicable***

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation 1272/2008, Annex VI

not listed

DI 2012/18/EU (Seveso III)

Category not subject

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

DI 1999/13/EC (VOC Guideline)

Component	Status
Trimethylolpropane (TMP) CAS: 77-99-6	not subject

International Inventories

Trimethylolpropane (TMP), CAS: 77-99-6

AICS (AU)***
DSL (CA)***
IECSC (CN)***
EC-No. 2010749 (EU)***
ENCS (2)-245 (JP)***
ISHL (2)-245 (JP)***
KECI KE-13838 (KR)***
INSQ (MX)***
PICCS (PH)***
TSCA (US)***
NZIoC-NZ May be used as single component chemical***
TCSI (TW)***

National regulatory information Great Britain

Releases to air (Pollution Inventory Substances)

Component	Annual reporting level threshold
Trimethylolpropane (TMP) CAS: 77-99-6	not listed

Releases to water (Pollution Inventory Substances)

not subject

Releases to sewer (Pollution Inventory Substances)

not subject

For details and further information please refer to the original regulation

15.2. Chemical safety assessment

The Chemical Safety Report (CSR) has been generated. For Exposure Scenarios see the annex.***

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H361fd: Suspected of damaging fertility. Suspected of damaging the unborn child.***

Abbreviations

A table of terms and abbreviations can be found under the following link:

http://echa.europa.eu/documents/10162/13632/information_requirements_r20_en.pdf

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

Training advice

For effective first-aid, special training / education is needed.

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on OQ owned data and public sources deemed valid or acceptable. The absence of data elements required by OSHA, ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

Further information for the safety data sheet

Changes against the previous version are marked by ***. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the OQ homepage (www.chemicals.oq.com).

Disclaimer

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. OQ makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

End of Safety Data Sheet

General information

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described below and you are unsure if they are also safe

Wear protective gloves/clothing and eye/face protection, where direct contact with substance is possible
For further specification, refer to section 8 of the SDS.***

1* Industrial use resulting in manufacture of another substance (use of intermediates)*****

2* Polymerisation*****

Number of the ES 1***

Short title of the exposure scenario

Industrial use resulting in manufacture of another substance (use of intermediates)***

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

SU9: Manufacture of fine chemicals***

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent***

Environmental release categories [ERC]

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)***

Product characteristics

Refer to attached safety data sheets***

Processes and activities covered by the exposure scenario

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

Use as an intermediate (not related to Strictly Controlled Conditions). Includes incidental exposures during recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).***

Further explanations

Industrial use

Assumes an advanced standard of occupational Health and Safety Management System***

Number of the contributing scenario

1***

Contributing exposure scenario controlling environmental exposure for ERC 6a***

Further specification

release factors for (Sp)ERC were modified Specific Environmental Release Categories [SPERC] SpERC ESVOC 6.1a.v1
assessment tool used: Chesar 3.5***

Amounts used

Daily amount per site: 23,15 to

Annual amount per site: 463 to

Fraction of EU tonnage used in region: 1***

Environment factors not influenced by risk management

River flow rate: 18000 m³/d***

Other given operational conditions affecting environmental exposure

Indoor/Outdoor use***

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0,01%

Release fraction to wastewater from process: 1%

Release fraction to soil from process: 0,1%***

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

The minimum grade of elimination in the sewage plant is (%): 40,83***

Conditions and measures related to external treatment of waste for disposal

Dispose of waste product or used containers according to local regulations***

Number of the contributing scenario

2***

Contributing exposure scenario controlling worker exposure for PROC 1***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Operating temperatures: =< 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance

substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

3***

Contributing exposure scenario controlling worker exposure for PROC 3, PROC 15***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Operating temperatures: =<110°C

Indoor use***

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Effectiveness of LEV (local exhaust ventilation):

90 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance
substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear respiratory protection (Efficiency: 90 %). For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

4***

Contributing exposure scenario controlling worker exposure for

PROC 4***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor use

Operating temperatures: =<110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a good standard of controlled ventilation (5 to 10 air changes per hour) . Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance
substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Wear respiratory protection (Efficiency: 90 %). For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

5***

Contributing exposure scenario controlling worker exposure for

PROC 8b***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor use

Operating temperatures: => 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a good standard of controlled ventilation (5 to 10 air changes per hour) . Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance
substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Wear respiratory protection (Efficiency: 95 %). For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario 6***
Contributing exposure scenario controlling worker exposure for PROC 9***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor use

Operating temperatures: => 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a good standard of controlled ventilation (5 to 10 air changes per hour) . Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance
substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Wear respiratory protection (Efficiency: 95 %). For further specification, refer to section 8 of the SDS.***

Fresh Water (Pelagic)	RCR: < 1***
Fresh Water (Sediment)	RCR: < 1***
Marine Water (Pelagic)	RCR: < 1***
Marine Water (Sediment)	RCR: < 1***
Air	RCR: < 1***
Agricultural Soil	RCR: < 1***
Sewage Treatment Plant (Effluent)	RCR: < 1***
Proc 1	combined routes RCR: < 1***
Proc 3	combined routes RCR: < 1***
Proc 4	combined routes RCR: < 1***
Proc 8b	combined routes RCR: < 1***
Proc 9	combined routes RCR: < 1***
Proc 15	combined routes RCR: < 1***

Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as $M(\text{site})$ [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])***

associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe***

Number of the ES 2***

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

Short title of the exposure scenario

Polymerisation***

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

SU12: Manufacture of plastics products, including compounding and conversion***

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC14: production of preparations or articles by tableting, compression, extrusion, pelettisation

PROC15: Use as laboratory reagent***

Environmental release categories [ERC]

ERC6c: Industrial use of monomers for manufacture of thermoplastics***

Product characteristics

Refer to attached safety data sheets***

Processes and activities covered by the exposure scenario

Manufacture of polymers from monomers in continuous and batch processes, including sparging, discharging and reactor maintenance and immediate polymer product formation (i.e. compounding, pelletisation, product off-gassing)***

Further explanations

Industrial use

Assumes an advanced standard of occupational Health and Safety Management System***

Number of the contributing scenario

1***

Contributing exposure scenario controlling environmental exposure for ERC 6c***

Further specification

release factors for (Sp)ERC were modified, assessment tool used: Chesar 3.5.***

Amounts used

Daily amount per site: 23.15 to

Annual amount per site: 463 to***

Environment factors not influenced by risk management

River flow rate: 18000 m³/d***

Other given operational conditions affecting environmental exposure

Indoor/Outdoor use***

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0.01%

Release fraction to wastewater from process: 0,01%

Release fraction to soil from process: 0%***

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

The minimum grade of elimination in the sewage plant is (%): 40,83***

Conditions and measures related to external treatment of waste for disposal

Dispose of waste product or used containers according to local regulations***

Number of the contributing scenario

2***

Contributing exposure scenario controlling worker exposure for PROC 1***

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Operating temperatures: =< 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance

substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

3***

Contributing exposure scenario controlling worker exposure for

PROC 2, PROC 3, PROC 15***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Operating temperatures: =< 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance

substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Wear respiratory protection (Efficiency: 90 %). For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

4***

Contributing exposure scenario controlling worker exposure for

PROC 4***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor use

Operating temperatures: =< 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a good standard of controlled ventilation (5 to 10 air changes per hour) . Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance

substance-handling procedures shall be well documented and supervised***

SAFETY DATA SHEET



Trimethylolpropane molten
10700

Version / Revision 2

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Wear respiratory protection (Efficiency: 90 %). For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

5***

Contributing exposure scenario controlling worker exposure for PROC 5***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

4 h (half shift)***

Other given operational conditions affecting workers exposure

Indoor use

Operating temperatures: =< 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a good standard of controlled ventilation (5 to 10 air changes per hour) . Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance
substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Respiratory protection: 95 %. For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

6***

Contributing exposure scenario controlling worker exposure for PROC 8b***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor use

Operating temperatures: =< 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a good standard of controlled ventilation (5 to 10 air changes per hour) . Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance
substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Wear respiratory protection (Efficiency: 95 %). For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

7***

Contributing exposure scenario controlling worker exposure for PROC 9***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

SAFETY DATA SHEET



**Trimethylolpropane molten
10700**

Version / Revision 2

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor use

Operating temperatures: =< 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a good standard of controlled ventilation (5 to 10 air changes per hour) . Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance
substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Respiratory protection: 95 %. For further specification, refer to section 8 of the SDS.***

Number of the contributing scenario

8***

Contributing exposure scenario controlling worker exposure for PROC 14***

Further specification

assessment tool used: Chesar 3.5***

Product characteristics

Covers percentage substance in the product up to 100 % (unless stated differently)

Liquid***

Frequency and duration of use

8 h (full shift)***

Other given operational conditions affecting workers exposure

Indoor use

Operating temperatures: =< 110°C***

Technical conditions and measures to control dispersion from source towards the worker

provide a good standard of controlled ventilation (5 to 10 air changes per hour) . Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative); 0 % (dermal).***

Organisational measures to prevent /limit releases, dispersion and exposure

Only properly trained and authorised personnel shall handle the substance
substance-handling procedures shall be well documented and supervised***

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable protective clothing. Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Wear respiratory protection (Efficiency: 95 %). For further specification, refer to section 8 of the SDS.***

Fresh Water (Pelagic)	RCR: < 1***
Fresh Water (Sediment)	RCR: < 1***
Marine Water (Pelagic)	RCR: < 1***
Marine Water (Sediment)	RCR: < 1***
Air	RCR: < 1***
Agricultural Soil	RCR: < 1***
Sewage Treatment Plant (Effluent)	RCR: < 1***
Proc 1	combined routes RCR: < 1***
Proc 2	combined routes RCR: < 1***
Proc 3	combined routes RCR: < 1***
Proc 4	combined routes RCR: < 1***
Proc 5	combined routes RCR: < 1***
Proc 8b	combined routes RCR: < 1***
Proc 9	combined routes RCR: < 1***
Proc 14	combined routes RCR: < 1***

SAFETY DATA SHEET



**Trimethylolpropane molten
10700**

Version / Revision 2

Proc 15

combined routes
RCR: < 1***

Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Usage of release factors allows downstream users to verify in a first approximation, if the combination of local usage and production conditions meets the defined release quantities resulting from this exposure scenario (calculated as M(site) [see amounts used, contributing scenario 1] x release factor [Technical conditions and measures at process level (source) to prevent release; contributing scenario 1])

For specific information regarding the SPERC used please refer to the ESIG webpage
www.esig.org/en/regulatory-information/reach/ges-library***

associated uses:

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe***