

SAFETY DATA SHEET



Isononanol

10320

Version / Revision

4.01

Revision Date

25-Jan-2022

Supersedes Version

4.00***

Issuing date

25-Jan-2022

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Identification of the substance/preparation

Isononanol

Chemical Name

3,5,5-Trimethylhexan-1-ol

CAS-No

3452-97-9

EC No.

222-376-7

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance / Preparation

Intermediate.

Uses advised against

None

1.3. Details of the supplier of the safety data sheet

Company/Undertaking Identification

OQ Chemicals GmbH
Rheinpromenade 4A
D-40789 Monheim
Germany

Product Information

Product Stewardship
FAX: +49 (0)208 693 2053
email: sc.psq@oq.com

1.4. Emergency telephone number

Emergency telephone number +44 (0) 1235 239 670 (UK) available 24/7
NCEC +1 202 464 2554

Local emergency telephone number

+61 2 8014 4558 (Australia)
18000 74234 (Australia toll-free number)
+64 9 929 1483 (New Zealand)
0800 446 881 (New Zealand toll-free number)
+65 3158 1195 (Sri Lanka)
007 803 011 0293 (Indonesia toll-free number)
+60 3 6207 4347 (Malaysia)
001 800 120 666 751 (Thailand toll-free number)
+65 3158 1200 (Bangladesh)
+63 2 8231 2149 (Philippines)
+84 28 4458 2388 (Vietnam)
+65 3165 2217 (Singapore)
available 24/7

SECTION 2: Hazards identification

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Europe

2.1. Classification of the substance or mixture

This substance is classified based on Directive 1272/2008/EC and its amendments (CLP Regulation)

Skin corrosion/irritation Category 2, H315
Serious eye damage/eye irritation Category 2, H319
Target Organ Systemic Toxicant - Repeated exposure Category 2, H373

Additional information

For full text of Hazard- and EU Hazard-statements see SECTION 16.

2.2. Label elements

Labelling according to Regulation 1272/2008/EC and its amendments (CLP Regulation).

Hazard pictograms



Signal word

Warning

Hazard statements

H315: Causes skin irritation.
H319: Causes serious eye irritation.
H373: May cause damage to organs through prolonged or repeated exposure if swallowed.

Precautionary statements

P260: Do not breathe gas/mist/vapours.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
P332 + P313: If skin irritation occurs: Get medical advice/ attention.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313: If eye irritation persists: Get medical advice/ attention.

2.3. Other hazards

Components of the product may be absorbed into the body by inhalation, ingestion and through the skin
Vapour/air-mixtures are explosive at intense warming

PBT and vPvB assessment Not required

USA

2.1. Classification of the substance or mixture

This substance is classified in accordance with paragraph (d) of §1910.1200 (GHS-US classification).

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Skin corrosion/irritation Category 2, H315
Serious eye damage/eye irritation Category 2A, H319
Target Organ Systemic Toxicant - Repeated exposure Category 2, H373
Flammable liquid Category 4, H227
Environmental hazard Aquatic Acute 2; H401

OSHA Specified Hazards Not applicable.

2.2. Label elements

Labeling according to §1910.1200 (GHS-US labeling).

Hazard symbol(s)



Signal word

Warning

Hazard statements

H227: Combustible liquid
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H373: May cause damage to organs through prolonged or repeated exposure if swallowed.
H401: Toxic to aquatic life

Precautionary statements

Prevention

P210: Keep away from flames and hot surfaces. - No smoking.
P280: Wear protective gloves/eye protection/face protection.
P264: Wash hands thoroughly after handling.
P260: Do not breathe gas/mist/vapours.
P273: Avoid release to the environment.

Response

P302 + P352: IF ON SKIN: Wash with plenty of water.
P332 + P313: If skin irritation occurs: Get medical advice/ attention.
P362 + P364: Take off contaminated clothing and wash it before reuse.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313: If eye irritation persists: Get medical advice/ attention.
P314: Get medical advice/attention if you feel unwell.

Storage

P403 + P235: Store in a well ventilated place. Keep cool.

Disposal

P501: Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

Components of the product may be absorbed into the body by inhalation, ingestion and through the skin
Vapour/air-mixtures are explosive at intense warming

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

SECTION 3: Composition / information on ingredients

3.1. Substances

Component	CAS-No	REACH-No	1272/2008/EC	Concentration (%)
3,5,5-Trimethylhexan-1-ol	3452-97-9	01-2119937262-41	Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT RE 2; H373	> 97,5

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Keep at rest. Aerate with fresh air. When symptoms persist or in all cases of doubt seek medical advice.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

Skin

Wash off immediately with plenty of water for at least 15 minutes. When symptoms persist or in all cases of doubt seek medical advice.

Ingestion

Call a physician immediately. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Main symptoms

cough, nausea, gastrointestinal discomfort, vomiting.

Special hazard

Lung irritation, Liver effects, Kidney disorders.

4.3. Indication of any immediate medical attention and special treatment needed

General advice

Remove contaminated, soaked clothing immediately and dispose of safely. First aider needs to protect himself.

Treat symptomatically. If ingested, irrigate the stomach using activated charcoal.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water spray

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Under conditions giving incomplete combustion, hazardous gases produced may consist of:
carbon monoxide (CO)
carbon dioxide (CO₂)
Combustion gases of organic materials must in principle be graded as inhalation poisons
Vapours are heavier than air and may spread along floors
Vapour/air-mixtures are explosive at intense warming

5.3. Advice for firefighters

Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Keep people away from and upwind of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: For personal protective equipment see section 8. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.
For emergency responders: Personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

6.3. Methods and material for containment and cleaning up

Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

Methods for cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. If liquid has been spilt in large quantities clean up promptly by scoop or vacuum. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

6.4. Reference to other sections

For personal protective equipment see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms.

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Advice on the protection of the environment

See Section 8: Environmental exposure controls.

Incompatible products

strong acids
strong oxidizing agents

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material. Vapour/air-mixtures are explosive at intense warming.

Technical measures/Storage conditions

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care.

Temperature class

T2

7.3. Specific end use(s)

Transported isolated intermediate (1907/2006)

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Exposure limits European Union

No exposure limits established

Exposure limits Germany

No exposure limits established.

Exposure limits United States of America

No exposure limits established regarding ACGIH, OSHA Z-1 and OSHA Z-2.

8.2. Exposure controls

Appropriate Engineering controls

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

Engineering and risk Management measures should maintain strictly controlled conditions. This also applies to environmental exposure controls.

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Personal protective equipment

General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe dust or mist. Ensure that eyewash stations and safety showers are close to the workstation location.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Hand protection

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

Suitable material	nitrile rubber
Reference substance	2-Ethylhexanol
Evaluation	according to EN 374: level 6
Glove thickness	approx 0,55 mm
Break through time	> 480 min

Suitable material	polyvinylchloride / nitrile rubber
Reference substance	2-Ethylhexanol
Evaluation	according to EN 374: level 6
Glove thickness	approx 0,9 mm
Break through time	> 480 min

Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

Respiratory protection

Respirator with filter for organic vapour. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Equipment should conform to NIOSH, EN or other applicable national standards.

Environmental exposure controls

If possible use in closed systems. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	colourless
Odour	alcoholic
Odour threshold	No data available
pH	No data available
Melting point/range	-80 °C @ 1013 hPa (Pour point)***
Boiling point/range	193,5 °C @ 1013 hPa

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Flash point 76 °C @ 1013 hPa***
Method ISO 2719
Evaporation rate No data available
Flammability (solid, gas) Does not apply, the substance is a liquid
Lower explosion limit No data available
Upper explosion limit No data available

Vapour pressure

Values [hPa]	Values [kPa]	Values [atm]	@ °C	@ °F	Method
2	0,2	0,002	20	68	
7,6	0,76	0,008	50	122	

Vapour density 5,0 (Air = 1) @ 20 °C (68 °F)

Relative density

Values	@ °C	@ °F	Method
0,8264	20	68	DIN 51757

Solubility 0,4 g/l @ 20 °C, in water, OECD 105

log Pow 3,7 (measured), OECD 117

Autoignition temperature 385 °C

Method EU A.15

Decomposition temperature No data available

Viscosity 14,19 mPa*s @ 20 °C

Method dynamic, ASTM D445***

Oxidizing properties Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties

Explosive properties Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties

9.2. Other information

Molecular weight 144,26

Molecular formula C₉H₂₀O

log Koc 3,11 calculated***

Refractive index 1,432 @ 20 °C***

Surface tension 38,0 mN/m (0,37 g/l @ 20°C (68°F)), OECD 115

SECTION 10: Stability and Reactivity

10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Vapour/air-mixtures are explosive at intense warming. Hazardous polymerisation does not occur.

10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

10.5. Incompatible materials

strong acids, strong oxidizing agents.

10.6. Hazardous decomposition products

No decomposition if used as directed.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure Ingestion, Inhalation, Eye contact, Skin contact

Acute toxicity				
3,5,5-Trimethylhexan-1-ol (3452-97-9)				
Routes of Exposure	Endpoint	Values	Species	Method
Oral	LD50	> 2000 mg/kg	rat, male/female	OECD 401
Oral	LD50	2300 mg/kg	rat, male/female	OECD 401
Dermal	LD50	2307 mg/kg	rabbit	OECD 402

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

Assessment

Based on available data, the classification criteria are not met for:

Acute oral toxicity

Acute dermal toxicity

Acute inhalation toxicity

An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration

Irritation and corrosion				
3,5,5-Trimethylhexan-1-ol (3452-97-9)				
Target Organ Effects	Species	Result	Method	
Skin	rabbit	Moderate skin irritation	OECD 404	4h
Eyes	rabbit	Mild eye irritation***	OECD 405	

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

Assessment

The available data lead to the classification given in section 2

For respiratory irritation, no data are available

Sensitization				
3,5,5-Trimethylhexan-1-ol (3452-97-9)				
Target Organ Effects	Species	Evaluation	Method	
Skin	Human experience	not sensitizing	OECD 406	

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

Assessment

Based on available data, the classification criteria are not met for:

Skin sensitization

For respiratory sensitization, no data are available

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Subacute, subchronic and prolonged toxicity				
3,5,5-Trimethylhexan-1-ol (3452-97-9)				
Type	Dose	Species	Method	
Subacute toxicity***	NOAEL: 12 mg/kg/d	rat, male/female	OECD 422	Oral
Subacute toxicity***	LOAEL: 60 mg/kg/d	rat, male/female	OECD 422	Oral

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

Assessment

The available data lead to the classification given in section 2

Carcinogenicity, Mutagenicity, Reproductive toxicity					
3,5,5-Trimethylhexan-1-ol (3452-97-9)					
Type	Dose	Species	Evaluation	Method	
Reproductive toxicity	NOAEL 300 mg/kg/d	rat, parental, male		OECD 422, Oral	
Reproductive toxicity	NOAEL 60 mg/kg/d	rat, parental, female		OECD 422, Oral	
Reproductive toxicity	NOAEL 12 mg/kg/d	rat, 1. Generation, male/female		OECD 422, Oral	
Mutagenicity		Salmonella typhimurium	negative	OECD 471 (Ames)	In vitro study
Mutagenicity		Escherichia coli	negative	OECD 472	In vitro study
Mutagenicity		CHL (Chinese hamster lung cells)***	negative	OECD 473 (Chromosomal Aberration)	In vitro study
Developmental Toxicity	NOAEL 12 mg/kg/d	rat		OECD 422	Maternal toxicity, Embryotoxicity
Developmental Toxicity	NOAEL 12 mg/kg/d	rat		OECD 422	Fetal toxicity
Developmental Toxicity	NOAEL 300 mg/kg/d	rat		OECD 422	Teratogenicity

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

CMR Classification

The available data on CMR properties are summarized in the table above. They do not indicate a classification into categories 1A or 1B

Evaluation

In vitro tests did not show mutagenic effects
No developmental effects in the absence of maternal toxicity

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

Main symptoms

cough, nausea, gastrointestinal discomfort, vomiting.

Target Organ Systemic Toxicant - Single exposure

Due to lack of data, a classification is not possible for:
STOT SE

Target Organ Systemic Toxicant - Repeated exposure

Liver effects
Kidney disorders

The available data lead to the classification given in section 2

Aspiration toxicity

Due to the viscosity, this product does not present an aspiration hazard

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Other adverse effects

Components of the product may be absorbed into the body by inhalation, ingestion and through the skin.

Note

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link:

<http://echa.europa.eu/information-on-chemicals/registered-substances>.

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity			
3,5,5-Trimethylhexan-1-ol (3452-97-9)			
Species	Exposure time	Dose	Method
Oryzias latipes (Medaka)	96h	LC50: 27,7 mg/l	OECD 203
Daphnia magna (Water flea)	48h	EC50: 6,77 mg/l***	OECD 202
Scenedesmus capricornutum (fresh water algae)	72h	EC50: > 33,3 mg/l (Biomass)	OECD 201
Scenedesmus capricornutum (fresh water algae)	72h	NOEC: 4,7 mg/l (Biomass)	OECD 201

Long term toxicity				
3,5,5-Trimethylhexan-1-ol (3452-97-9)				
Type	Species	Dose	Method	
Mortality	Daphnia magna (Water flea)	LC50: > 3,87 mg/l	OECD 202	21 d
Reproductive toxicity	Daphnia magna (Water flea)	EC50: 2,09 mg/l	OECD 202	21 d
Aquatic toxicity***	Oryzias latipes (Medaka)	LC50: > 17 mg/l	OECD 204	14 d***
Aquatic toxicity***	Oryzias latipes (Medaka)	NOEC: 1,28 mg/l	OECD 204	14 d***
Aquatic toxicity***	Scenedesmus capricornutum (fresh water algae)***	NOEC: 10,3 mg/l Growth rate***	OECD 201***	3 d***

Terrestrial toxicity				
3,5,5-Trimethylhexan-1-ol (3452-97-9)				
Species	Exposure time	Dose	Type	Method
Xenopus laevis (African clawed frog)***	48 h***	LC50: 13,5 mg/l***	Mortality***	

12.2. Persistence and degradability

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

Biodegradation

3,67 % (28 d), BOD, activated sludge, Not readily biodegradable, OECD 301 C.***

Abiotic Degradation		
3,5,5-Trimethylhexan-1-ol (3452-97-9)		
Type	Result	Method
Hydrolysis***	not expected***	

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

Photolysis***	Half-life (DT50): 36 h***	calculated***
---------------	---------------------------	---------------

12.3. Bioaccumulative potential

3,5,5-Trimethylhexan-1-ol (3452-97-9)		
Type	Result	Method
BCF	3,9 - 8,1 @ 100 µg/l	OECD 305 C
log Pow	3,7 @ 25 °C (77 °F)***	measured, OECD 117

12.4. Mobility in soil

3,5,5-Trimethylhexan-1-ol (3452-97-9)		
Type	Result	Method
Surface tension	38,0 mN/m (0,37 g/l @ 20°C (68°F))	OECD 115
Adsorption/Desorption***	log Koc: 3,11***	calculated***
Distribution to environmental compartments***	Air: 9,9 % Soil: 83,1 % Water: 6,2 % Sediment: 0,8 %***	Calculation according Mackay, Level III***

12.5. Results of PBT and vPvB assessment

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

PBT and vPvB assessment

Not required

12.6. Other adverse effects

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product Information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Hazardous waste according to European Waste Catalogue (EWC)

Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SECTION 14: Transport information

Section 14.1 - 14.6

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

ICAO-TI / IATA-DGR

Not restricted

IMDG

Not restricted

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Product name	Nonyl alcohol
Ship type	2
Pollution category	Y

ADR/RID

Not restricted

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation 1272/2008, Annex VI not listed

DI 2012/18/EU (Seveso III)

Category not subject

DI 1999/13/EC (VOC Guideline)

Component	Status
3,5,5-Trimethylhexan-1-ol CAS: 3452-97-9	regulated

International Inventories

3,5,5-Trimethylhexan-1-ol, CAS: 3452-97-9

AICS (AU)
DSL (CA)
IECSC (CN)
EC-No. 2223767 (EU)
ENCS (2)-217 (JP)
ISHL (2)-217 (JP)
KECI KE-34566 (KR)
PICCS (PH)
TSCA (US)
NZIoC (NZ)***
TCSI (TW)

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H315: Causes skin irritation.

SAFETY DATA SHEET



Isononanol
10320

Version / Revision 4.01

H319: Causes serious eye irritation.

H373: May cause damage to organs through prolonged or repeated exposure if swallowed.

Abbreviations

A table of terms and abbreviations can be found under the following link:

http://echa.europa.eu/documents/10162/13632/information_requirements_r20_en.pdf

Training advice

For effective first-aid, special training / education is needed.

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on OQ owned data and public sources deemed valid or acceptable. The absence of data elements required by OSHA, ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

Further information for the safety data sheet

Observe national and local legal requirements. Changes against the previous version are marked by ***.

The annex is not required because the substance is registered as an intermediate under REACH

Disclaimer

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. OQ makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

End of Safety Data Sheet