

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision
Supersedes Version

5
4.02***

Revision Date
Issuing date

27-Oct-2022
27-Oct-2022

SECTION 1: Identification of the substance / mixture and of the company / undertaking

1.1. Product identifier

Identification of the
substance/preparation

n-Butanol

CAS-No. 71-36-3
EC No. 200-751-6
Registration number (REACH) 01-2119484630-38

1.2. Relevant identified uses of the substance or mixture and uses advised against

| | |
|----------------------|--|
| Identified uses | Intermediate Formulation Distribution of substance coatings cleaning agent Lubricants and lubricant additives Metal working fluids / rolling oils laboratory chemicals Polymer processing consumer care product |
| Uses advised against | None |

1.3. Details of the supplier of the safety data sheet

| | |
|---------------------------------------|---|
| Company/Undertaking Identification | OQ Chemicals GmbH Rheinpromenade 4A D-40789 Monheim Germany |
|---------------------------------------|---|

| | |
|---------------------|---|
| Product Information | Product Stewardship FAX: +49 (0)208 693 2053 email: sc.psq@oq.com |
|---------------------|---|

1.4. Emergency telephone number

| | |
|--|---|
| Emergency telephone number | +44 (0) 1235 239 670 (UK) available 24/7 |
| National emergency telephone number | National Poisons Information Centre +353 (0)1 809 2166 available to the public 8 am - 10 pm +353 (0)1 809 2566 available 24/7 for medical professionals |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

This substance is classified based on Directive 1272/2008/EC and its amendments (CLP Regulation)

Flammable liquid Category 3, H226
Acute oral toxicity Category 4, H302
Skin corrosion/irritation Category 2, H315
Serious eye damage/eye irritation Category 1, H318
Target Organ Systemic Toxicant - Single exposure Category 3, H335, Category 3, H336

Additional information

For full text of Hazard- and EU Hazard-statements see SECTION 16.

2.2. Label elements

Labelling according to Regulation 1272/2008/EC and its amendments (CLP Regulation).

Hazard pictograms



Signal word

Danger

Hazard statements

H226: Flammable liquid and vapour.
H302: Harmful if swallowed.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.

Precautionary statements

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing gas/mist/vapours.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303 + P361 + P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a POISON CENTER/doctor.
P403 + P235: Store in a well ventilated place. Keep cool.

2.3. Other hazards

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback
Vapours may form explosive mixture with air
Components of the product may be absorbed into the body by inhalation, ingestion and through the skin

PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Endocrine disrupting assessments

The substance is not listed on the candidate list according to Art. 59(1), REACH. The substance was not assessed as having endocrine disrupting properties according to regulation 2017/2100/EU or 2018/605/EU.

SECTION 3: Composition / information on ingredients

3.1. Substances

| Component | CAS-No | REACH-No | 1272/2008/EC | Concentration (%) |
|------------|---------|------------------|---|-------------------|
| Butan-1-ol | 71-36-3 | 01-2119484630-38 | Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3; H336 | > 99,80 |

For full text of Hazard- and EU Hazard-statements see SECTION 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Keep at rest. Aerate with fresh air. When symptoms persist or in all cases of doubt seek medical advice.

Skin

Wash off immediately with soap and plenty of water. When symptoms persist or in all cases of doubt seek medical advice.

Eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. Immediate medical attention is required.

Ingestion

Rinse mouth. Call a physician immediately. If conscious, drink plenty of water. Do not induce vomiting without medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Main symptoms

cough, headache, dizziness, drowsiness, nausea, vomiting, abdominal pain, unconsciousness, diarrhea.

Special hazard

Lung irritation, Pneumonia.

4.3. Indication of any immediate medical attention and special treatment needed

General advice

Remove contaminated, soaked clothing immediately and dispose of safely. If unconscious place in recovery position and seek medical advice. First aider needs to protect himself.

Treat symptomatically. If ingested, irrigate the stomach using activated charcoal. Chemical pneumonitis could follow respiratory exposure.

SECTION 5: Firefighting measures

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

5.1. Extinguishing media

Suitable extinguishing media

dry chemical, carbon dioxide (CO₂), water spray, alcohol-resistant foam

Unsuitable Extinguishing Media

Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Under conditions giving incomplete combustion, hazardous gases produced may consist of:

carbon monoxide (CO)

carbon dioxide (CO₂)

Combustion gases of organic materials must in principle be graded as inhalation poisons

Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback

Vapours may form explosive mixture with air

5.3. Advice for firefighters

Special protective equipment for firefighters

Fire fighter protection should include a self-contained breathing apparatus (NIOSH-approved or EN 133) and full fire-fighting turn out gear.

Precautions for firefighting

Cool containers / tanks with water spray. Dike and collect water used to fight fire. Keep people away from and upwind of fire. Do not allow run-off from fire fighting to enter drains or water courses. Foam should be applied in large quantities as it is broken down to some extent by the product.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: For personal protective equipment see section 8. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep people away from and upwind of spill/leak. Ensure adequate ventilation, especially in confined areas. Keep away from heat and sources of ignition.

For emergency responders: Personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage. Do not discharge product into the aquatic environment without pretreatment (biological treatment plant).

6.3. Methods and material for containment and cleaning up

Methods for containment

Stop the flow of material, if possible without risk. Dike spilled material, where this is possible.

Methods for cleaning up

Soak up with inert absorbent material (e.g. universal binder). Keep in suitable, closed containers for disposal. If liquid has been spilt in large quantities clean up promptly by scoop or vacuum. Dispose of in accordance with local regulations. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).

6.4. Reference to other sections

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

For personal protective equipment see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Further info may be available in the appropriate Exposure scenarios in the annex to this SDS.

Advice on safe handling

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and/or exhaust in work rooms.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Incompatible products

strong oxidizing agents
acids
acid chlorides
reducing agents

7.2. Conditions for safe storage, including any incompatibilities

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). In case of fire, emergency cooling with water spray should be available. Ground and bond containers when transferring material. Vapour is heavier than air and can travel considerable distance to a source of ignition and flashback. Vapours may form explosive mixture with air.

Technical measures/Storage conditions

Keep containers tightly closed in a cool, well-ventilated place. Handle and open container with care.

Suitable material

stainless steel, mild steel

Unsuitable material

Attacks some forms of plastic and rubber, Natural Rubber

Temperature class

T2

7.3. Specific end use(s)

Intermediate

Formulation

Distribution of substance

coatings

cleaning agent

Lubricants and lubricant additives

Metal working fluids / rolling oils

laboratory chemicals

Polymer processing

consumer care product

For specific end use information see the annex of this safety data sheet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

SECTION 8: Exposure controls / personal protection

8.1. Control parameters

Exposure limits European Union

No exposure limits established

Exposure limits Ireland

Ireland OELs

| Component | TWA (mg/m ³) | TWA (ppm) | STEL (mg/m ³) | STEL (ppm) | Skin Absorption | Sensitizer |
|----------------------------|--------------------------|-----------|---------------------------|------------|-----------------|------------|
| Butan-1-ol CAS: 71-36-3 | | 20 | | | | |

Notes

For details and further information please refer to the original regulation.

DNEL & PNEC

Butan-1-ol, CAS: 71-36-3

Workers

| | |
|---|--------------------------------------|
| DN(M)EL - long-term exposure - systemic effects - Inhalation | Low hazard (no threshold derived) |
| DN(M)EL - acute / short-term exposure - systemic effects - Inhalation | No hazard identified |
| DN(M)EL - long-term exposure - local effects - Inhalation | 310 mg/m ³ |
| DN(M)EL - acute / short-term exposure - local effects - Inhalation | Low hazard (no threshold derived) |
| DN(M)EL - long-term exposure - systemic effects - Dermal | Low hazard (no threshold derived) |
| DN(M)EL - acute / short-term exposure - systemic effects - Dermal | No hazard identified |
| DN(M)EL - long-term exposure - local effects - Dermal | Low hazard (no threshold derived) |
| DN(M)EL - acute / short-term exposure - local effects - Dermal | Low hazard (no threshold derived) |
| DN(M)EL - local effects - eyes | Medium hazard (no threshold derived) |

General population

| | |
|---|-----------------------------------|
| DN(M)EL - long-term exposure - systemic effects - Inhalation | 55,357 mg/m ³ |
| DN(M)EL - acute / short-term exposure - systemic effects - Inhalation | No hazard identified |
| DN(M)EL - long-term exposure - local effects - Inhalation | 155 mg/m ³ |
| DN(M)EL - acute / short-term exposure - local effects - Inhalation | Low hazard (no threshold derived) |
| DN(M)EL - long-term exposure - systemic effects - Dermal | 3,125 mg/kg bw/day |
| DN(M)EL - acute / short-term exposure - systemic effects - Dermal | No hazard identified |
| DN(M)EL - long-term exposure - local effects - Dermal | Low hazard (no threshold derived) |
| DN(M)EL - acute / short-term exposure - local effects - Dermal | Low hazard (no threshold derived) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

DN(M)EL - long-term exposure - systemic effects - Oral
DN(M)EL - acute / short-term exposure - systemic effects - Oral
DN(M)EL - local effects - eyes

derived)
1,562 mg/kg bw/day
No hazard identified
Medium hazard (no threshold derived)

Environment

| | |
|--|----------------------------------|
| PNEC aqua - freshwater | 0,082 mg/l |
| PNEC aqua - marine water | 0,008 mg/l |
| PNEC aqua - intermittent releases | 2,25 mg/l |
| PNEC STP | 2476 mg/l |
| PNEC sediment - freshwater | 0,324 mg/kg dw |
| PNEC sediment - marine water | 0,032 mg/kg dw |
| PNEC Air | No hazard identified |
| PNEC soil | 0,166 mg/kg dw |
| Secondary poisoning | No potential for bioaccumulation |

8.2. Exposure controls

Special adaptations (REACH)

Not applicable.

Appropriate Engineering controls

General or dilution ventilation is frequently insufficient as the sole means of controlling employee exposure. Local ventilation is usually preferred. Explosion-proof equipment (for example fans, switches, and grounded ducts) should be used in mechanical ventilation systems.

Personal protective equipment

General industrial hygiene practice

Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist. Ensure that eyewash stations and safety showers are close to the workstation location.

Hygiene measures

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product.

Eye protection

Tightly fitting safety goggles. In addition to goggles, wear a face shield if there is a reasonable chance for splash to the face.

Equipment should conform to EN 166

Hand protection

Wear protective gloves. Recommendations are listed below. Other protective material may be used, depending on the situation, if adequate degradation and permeation data is available. If other chemicals are used in conjunction with this chemical, material selection should be based on protection for all chemicals present.

| | |
|---------------------------|------------------------------|
| Suitable material | butyl-rubber |
| Evaluation | according to EN 374: level 6 |
| Glove thickness | approx 0,3 mm |
| Break through time | > 480 min |

| | |
|--------------------------|------------------------------|
| Suitable material | nitrile rubber |
| Evaluation | according to EN 374: level 6 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Glove thickness approx 0,55 mm
Break through time > 480 min

Skin and body protection

Impervious clothing. Wear face-shield and protective suit for abnormal processing problems.

Respiratory protection

Respirator with A filter. Full mask with above mentioned filter according to producers using requirements or self-contained breathing apparatus. Equipment should conform to EN 136 or EN 140 and EN 143.

Environmental exposure controls

If possible use in closed systems. If leakage can not be prevented, the substance needs to be suck off at the emersion point, if possible without danger. Observe the exposure limits, clean exhaust air if needed. If recycling is not practicable, dispose of in compliance with local regulations. Inform the responsible authorities in case of leakage into the atmosphere, or of entry into waterways, soil or drains.

Additional advice

Further details on substance data can be found in the registration dossier under the following link:
<http://echa.europa.eu/information-on-chemicals/registered-substances>. For specific exposure controls see the annex to this safety data sheet.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | | | | | |
|---|-------------------------------------|--------------|------|------|----------------|
| Physical state | liquid*** | | | | |
| Colour | colourless | | | | |
| Odour | alcoholic | | | | |
| Odour threshold | No data available | | | | |
| Melting point/freezing point | < -90 °C (Pour point) | | | | |
| Boiling point or initial boiling point and boiling range | 119 °C @ 1013 hPa | | | | |
| Method | OECD 103 | | | | |
| Flammability | Ignitable | | | | |
| Lower explosion limit | 1,4 Vol % | | | | |
| Upper explosion limit | 11,3 Vol % | | | | |
| Flash point | 35 °C @ 1013 hPa | | | | |
| Method | ISO 2719 | | | | |
| Autoignition temperature | 355 °C @ 1013 hPa | | | | |
| Method | DIN 51794 | | | | |
| Decomposition temperature | No data available | | | | |
| pH | neutral | | | | |
| Kinematic Viscosity | 3,638 mm ² /s @ 20 °C*** | | | | |
| Method | DIN 51562*** | | | | |
| Solubility | 66 g/l @ 20 °C, in water, OECD 105 | | | | |
| Partition coefficient n-octanol/water (log value) | 1 @ 25 °C (77 °F) OECD 117 | | | | |
| Vapour pressure | | | | | |
| Values [hPa] | Values [kPa] | Values [atm] | @ °C | @ °F | Method |
| 10 | 1 | 0,010 | 20 | 68 | DIN EN 13016-2 |
| 53 | 5,3 | 0,052 | 50 | 122 | DIN EN 13016-2 |
| Density and/or relative density | | | | | |
| Values | @ °C | @ °F | | | Method |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

0,81 20 68 DIN 51757
Relative vapour density 2,6 (Air = 1) @ 20 °C (68 °F)
Particle characteristics not applicable

9.2. Other information

Explosive properties Does not apply, substance is not explosive. There are no chemical groups associated with explosive properties
Oxidizing properties Does not apply, substance is not oxidising. There are no chemical groups associated with oxidizing properties
Molecular weight 74,12
Molecular formula C4 H10 O
log Koc 0,54 calculated
Refractive index 1,399 @ 20 °C
Surface tension 69,9 mN/m (1 g/l @ 20°C (68°F)), OECD 115
Evaporation rate No data available

SECTION 10: Stability and Reactivity

10.1. Reactivity

The reactivity of the product corresponds to the typical reactivity shown by the substance group as described in any text book on organic chemistry.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Vapours may form explosive mixture with air.

10.4. Conditions to avoid

Avoid contact with heat, sparks, open flame and static discharge. Avoid any source of ignition.

10.5. Incompatible materials

strong oxidizing agents, acids, acid chlorides, reducing agents.

10.6. Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Likely routes of exposure Ingestion, Inhalation, Eye contact, Skin contact

| Acute toxicity | | | | |
|-----------------------------|----------|------------|-------------|----------|
| Butan-1-ol (71-36-3) | | | | |
| Routes of Exposure | Endpoint | Values | Species | Method |
| Oral | LD50 | 2292 mg/kg | rat, female | OECD 401 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

| | | | | |
|------------|------|-------------------|------------------|----------|
| Inhalative | LC0 | > 17,76 mg/l (4h) | rat, male/female | OECD 403 |
| Dermal | LD50 | 3430 mg/kg | rabbit male | OECD 402 |

Butan-1-ol, CAS: 71-36-3

Assessment

Based on available data, the classification criteria are not met for:

Acute oral toxicity

Acute dermal toxicity

Acute inhalation toxicity

Irritation and corrosion

Butan-1-ol (71-36-3)

| Target Organ Effects | Species | Result | Method | |
|----------------------|---------|--------------------------|----------|----------|
| Skin | rabbit | irritating | | 2h |
| Eyes | rabbit | severe irritation | OECD 405 | |
| Respiratory tract | human | irritating (up 200 ppm) | | 10 years |
| Respiratory tract | human | Low irritating potential | | 5 min |
| Respiratory tract | rat | irritating | | 7h |

Butan-1-ol, CAS: 71-36-3

Assessment

The available data lead to the classification given in section 2

Sensitization

Butan-1-ol (71-36-3)

| Target Organ Effects | Species | Evaluation | Method | |
|----------------------|------------|-----------------|--------|--------------------------------|
| Skin | guinea pig | not sensitizing | | read across Weight of evidence |

Butan-1-ol, CAS: 71-36-3

Assessment

Based on available data, the classification criteria are not met for:

Skin sensitization

For respiratory sensitization, no data are available

Subacute, subchronic and prolonged toxicity

Butan-1-ol (71-36-3)

| Type | Dose | Species | Method | |
|---------------------|----------------------------|------------------|------------------|------------------------|
| Subchronic toxicity | NOAEL: 125 mg/kg/d | rat, male/female | | Oral |
| Subchronic toxicity | LOAEL: 500 mg/kg/d (90d) | rat, male/female | | Oral |
| Subchronic toxicity | NOAEL: ~ 2,35 mg/l/d (90d) | rat, male/female | EPA OTS 798.2450 | Inhalation read across |

Butan-1-ol, CAS: 71-36-3

Assessment

Based on available data, the classification criteria are not met for:

STOT RE

Carcinogenicity, Mutagenicity, Reproductive toxicity

Butan-1-ol (71-36-3)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

| Type | Dose | Species | Evaluation | Method | |
|------------------------|------------------------------|---------------------------------------|------------|--|--------------------------------------|
| Mutagenicity | | V79 cells, Chinese hamster | negative | OECD 476 (Mammalian Gene Mutation) HPRT | In vitro study |
| Mutagenicity | | V79 cells, Chinese hamster | negative | Chromosomal Aberration | In vitro study |
| Mutagenicity | | Salmonella typhimurium | negative | Ames test | |
| Mutagenicity | | mouse male/female | negative | OECD 474 | Oral in vivo micronucleus test |
| Reproductive toxicity | NOAEL 18,5 mg/l | rat, parental | | | Inhalation |
| Reproductive toxicity | NOAEL 18,5 mg/l | rat, 1. Generation, male/female | | | Inhalation |
| Reproductive toxicity | NOAEL 5000 mg/kg/d | rat, parental, female | | Oral Systemic toxicity | |
| Developmental Toxicity | NOAEL 1454 mg/kg/d | rat | | OECD 414, Oral | Maternal toxicity, Fetal toxicity |
| Developmental Toxicity | NOAEL 5654 mg/kg/d | rat | | OECD 414, Oral | Teratogenicity |
| Developmental Toxicity | NOAEL 10,8 mg/l | rat | | Inhalation | Maternal toxicity, Fetal toxicity |
| Developmental Toxicity | NOAEL 24,7 mg/l | rat | | Inhalation | Teratogenicity |
| Carcinogenicity | no carcinogenic potential | | | QSAR | |
| Reproductive toxicity | NOAEL 500 mg/kg/d | rat, male/female | | Oral | |
| Reproductive toxicity | NOAEC: 2000 ppm | rat, male/female | | OECD 416 Inhalation | Fertility read across |
| Reproductive toxicity | LOEL: 300 mg/kg/d | rat, 1. Generation, male/female | | Oral | |

Butan-1-ol, CAS: 71-36-3

CMR Classification

The available data on CMR properties are summarized in the table above. They do not indicate a classification into categories 1A or 1B

Evaluation

In vitro tests did not show mutagenic effects

Did not show mutagenic effects in animal experiments

In the absence of specific alerts no cancer testing is required

Butan-1-ol, CAS: 71-36-3

Main symptoms

cough, headache, dizziness, drowsiness, nausea, vomiting, abdominal pain, unconsciousness, diarrhoea.

Target Organ Systemic Toxicant - Single exposure

The available data lead to the classification given in section 2

Target Organ Systemic Toxicant - Repeated exposure

Based on available data, the classification criteria are not met for:

STOT RE

Aspiration toxicity

Based on the viscosity a potential aspiration hazard cannot be excluded

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

11.2. Information on other hazards

Endocrine disrupting properties

The substance has not been identified as having endocrine disrupting properties in accordance with section 2.3.

Butan-1-ol, CAS: 71-36-3

Other adverse effects

Components of the product may be absorbed into the body by inhalation, ingestion and through the skin.

Note

Handle in accordance with good industrial hygiene and safety practice. Further details on substance data can be found in the registration dossier under the following link:

<http://echa.europa.eu/information-on-chemicals/registered-substances>.

SECTION 12: Ecological information

12.1. Toxicity

| Acute aquatic toxicity | | | |
|--------------------------------------|---------------|------------------------------|-------------------|
| Butan-1-ol (71-36-3) | | | |
| Species | Exposure time | Dose | Method |
| Pimephales promelas (fathead minnow) | 96h | LC50: 1376 mg/l | OECD 203 |
| Daphnia magna (Water flea) | 48h | EC50: 1328 mg/l | OECD 202 |
| Pseudokirchneriella subcapitata | 96h | EC50: 225 mg/l (Growth rate) | OECD 201 |
| Pseudomonas putida | 17 h | EC50: 4390 mg/l | DIN 38412, part 8 |

| Long term toxicity | | | |
|-----------------------------|---------------------------------|---|----------------------|
| Butan-1-ol (71-36-3) | | | |
| Type | Species | Dose | Method |
| Reproductive toxicity | Daphnia magna (Water flea) | NOEC: 4,1 mg/l (21d) | OECD 211 |
| Reproductive toxicity | Daphnia magna (Water flea) | EC50: 18 mg/l/21d | OECD 211 |
| Aquatic toxicity | Pseudokirchneriella subcapitata | EC10: 134 mg/l (96 h) NOAEC: 129 mg/l (96 h) | OECD 201 Growth rate |

| Terrestrial toxicity | | | | |
|-----------------------------|---------------|------------------|-------------|-----------------------------|
| Butan-1-ol (71-36-3) | | | | |
| Species | Exposure time | Dose | Type | Method |
| Lactuca sativa (Lettuce) | 3 d | EC50: ~ 390 mg/l | germination | germination inhibition test |

12.2. Persistence and degradability

Butan-1-ol, CAS: 71-36-3

Biodegradation

92 % (15 d), Sewage, aerobic, domestic, non-adapted, BOD.

| Abiotic Degradation | | |
|-----------------------------|--------|--------|
| Butan-1-ol (71-36-3) | | |
| Type | Result | Method |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

| | | |
|------------|-------------------------------|----------|
| Hydrolysis | No data available | |
| Photolysis | Half-life (DT50): 46 - 53,5 h | measured |

12.3. Bioaccumulative potential

| Butan-1-ol (71-36-3) | | |
|----------------------|-----------|------------|
| Type | Result | Method |
| log Pow | 1 @ 25 °C | OECD 117 |
| BCF | 3,16 | calculated |

12.4. Mobility in soil

| Butan-1-ol (71-36-3) | | |
|--|---|---------------------------------------|
| Type | Result | Method |
| Surface tension | 69,9 mN/m (1 g/l @ 20°C (68°F)) | OECD 115 |
| Adsorption/Desorption | log Koc: 0,54 | calculated |
| Distribution to environmental compartments | Air: 27,07 Soil: 0,04 Water: 72,85 Sediment: 0,04 Suspended sediment: 0 Biota: 0 | Calculation according Mackay, Level I |

12.5. Results of PBT and vPvB assessment

Butan-1-ol, CAS: 71-36-3

PBT and vPvB assessment

This substance is not considered to be persistent, bioaccumulating nor toxic (PBT), nor very persistent nor very bioaccumulating (vPvB)

12.6. Endocrine disrupting properties

The substance has not been identified as having endocrine disrupting properties in accordance with section 2.3.

12.7. Other adverse effects

Butan-1-ol, CAS: 71-36-3

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product Information

Disposal required in compliance with all waste management related state and local regulations. The choice of the appropriate method of disposal depends on the product composition by the time of disposal as well as the local statutes and possibilities for disposal.

Hazardous waste according to European Waste Catalogue (EWC)

Uncleaned empty packaging

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

SECTION 14: Transport information

ADR/RID

| | |
|---|----------|
| 14.1. UN number or ID number | UN 1120 |
| 14.2. UN proper shipping name | Butanols |
| 14.3. Transport hazard class(es) | 3 |
| 14.4. Packing group | III |
| 14.5. Environmental hazards | no |
| 14.6. Special precautions for user | |
| ADR Tunnel restriction code | (D/E) |
| Classification Code | F1 |
| Hazard Number | 30 |

ADN

ADN: Container and Tanker

| | |
|---|----------|
| 14.1. UN number or ID number | UN 1120 |
| 14.2. UN proper shipping name | Butanols |
| 14.3. Transport hazard class(es) | 3 |
| 14.4. Packing group | III |
| 14.5. Environmental hazards | no |
| 14.6. Special precautions for user | |
| Classification Code | F1 |
| Hazard Number | 30 |

ICAO-TI / IATA-DGR

| | |
|---|-------------------|
| 14.1. UN number or ID number | UN 1120 |
| 14.2. UN proper shipping name | Butanols |
| 14.3. Transport hazard class(es) | 3 |
| 14.4. Packing group | III |
| 14.5. Environmental hazards | no |
| 14.6. Special precautions for user | no data available |

IMDG

| | |
|--|-----------------|
| 14.1. UN number or ID number | UN 1120 |
| 14.2. UN proper shipping name | Butanols |
| 14.3. Transport hazard class(es) | 3 |
| 14.4. Packing group | III |
| 14.5. Environmental hazards | no |
| 14.6. Special precautions for user | |
| EmS | F-E, S-D |
| 14.7. Maritime transport in bulk according to IMO instruments | *** |
| Product name | n-Butyl alcohol |
| Ship type | 3 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Pollution category Z
Hazard class P***

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation 1272/2008, Annex VI

Butan-1-ol, CAS: 71-36-3

Classification Flam. Liq. 3; H226
Acute Tox. 4*; H302
STOT SE 3; H335
Skin Irrit. 2; H315
Eye Dam. 1; H318
STOT SE 3; H336

Hazard pictograms GHS02 Flame
GHS05 Corrosion
GHS07 Exclamation mark

Signal word Danger

Hazard statements H226, H302, H335, H315, H318, H336

DI 2012/18/EU (Seveso III)

Category Annex I, part 1:
P5a - c; depending on conditions

DI 1999/13/EC (VOC Guideline)

| Component | Status |
|----------------------------|-----------|
| Butan-1-ol CAS: 71-36-3 | regulated |

International Inventories

Butan-1-ol, CAS: 71-36-3

AICS (AU)
DSL (CA)
IECSC (CN)
EC-No. 2007516 (EU)
ENCS (2)-3049 (JP)
ISHL (2)-3049 (JP)
ISHL 2-(8)-299 (JP)
KECI KE-03867 (KR)
INSQ (MX)
PICCS (PH)
TSCA (US)
NZIoC (NZ)***
TCSI (TW)

15.2. Chemical safety assessment

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

The Chemical Safety Report (CSR) has been generated. For Exposure Scenarios see the annex.

SECTION 16: Other information

Full text of H-Statements referred to under sections 2 and 3

H226: Flammable liquid and vapour.
H302: Harmful if swallowed.
H315: Causes skin irritation.
H318: Causes serious eye damage.
H335: May cause respiratory irritation.
H336: May cause drowsiness or dizziness.

Abbreviations

A table of terms and abbreviations can be found under the following link:
http://echa.europa.eu/documents/10162/13632/information_requirements_r20_en.pdf

Training advice

For effective first-aid, special training / education is needed.

Sources of key data used to compile the datasheet

Information contained in this safety data sheet is based on OQ owned data and public sources deemed valid or acceptable. The absence of data elements required by OSHA, ANSI or Annex II, Regulation 1907/2006/EC indicates, that no data meeting these requirements is available.

Further information for the safety data sheet

Changes against the previous version are marked by ***. Observe national and local legal requirements. For more information, other material safety data sheets or technical data sheets please consult the OQ homepage (www.chemicals.oq.com).

Disclaimer

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. OQ Chemicals makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards.

End of Safety Data Sheet

Annex to the extended Safety Data Sheet (eSDS)

General information

For consumer applications in the following usage areas please contact OQ (sc.psq@oq.com):

Uses in coatings
Use in Cleaning Agents
Lubricants

Consumer uses e.g. as a carrier in cosmetics/personal care products, perfumes and fragrances. Note: For cosmetic and personal care products, risk assessment only required for the environment under REACH as human health is covered by alternative legislation

Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described below and you are unsure if they are also safe

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

For specific information regarding the SPERC used please refer to the ESIG webpage
<https://www.esig.org/reach-ges/environment/>

A quantitative approach used to conclude safe use for:

Environmental compartment

Long term local hazards via inhalation

Long-term Systemic effects via inhalation

A qualitative approach used to conclude safe use for:

For dermal/eye local exposure

Operational conditions and risk management measures

Following operational conditions and risk management measures, are based on qualitative risk characterisation:

Avoid frequent and direct contact with substance

Wear protective gloves and eye/face protection

Minimization of manual phases

Supervision in place to check that the RMMs in place are being used correctly and OCs followed.

Exposure scenario identification

- 1 **Industrial use resulting in manufacture of another substance (use of intermediates)**
- 2 **Formulation & (re)packing of substances and mixtures**
- 3 **Distribution of substance**
- 4 **Uses in coatings**
- 5 **Uses in coatings**
- 6 **Use in Cleaning Products**
- 7 **Use in Cleaning Products**
- 8 **Lubricants**
- 9 **Lubricants**
- 10 **Metal working fluids / rolling oils**
- 11 **Metal working fluids / rolling oils**
- 12 **Use in laboratories**
- 13 **Polymer processing**

Number of the ES 1

Short title of the exposure scenario

Industrial use resulting in manufacture of another substance (use of intermediates)

List of use descriptors

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

SU8: Manufacture of bulk, large scale chemicals (including petroleum products)

SU9: Manufacture of fine chemicals

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Environmental release categories [ERC]

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Manufacture of the substance or use as an intermediate, process chemical or extracting agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

Further explanations

Industrial use

assessment tool used:

Chesar 3.2

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes an advanced standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario 1
Contributing exposure scenario controlling environmental exposure for ERC 6a

Amounts used

Daily amount per site: 735.5 to

Annual amount per site: 242705 to

Fraction of EU tonnage used in region: 1

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 5E-3%

Release fraction to wastewater from process: 2%

Release fraction to soil from process: 0.1%

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 99.9 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 99.99 %

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

Do not apply industrial sludge to natural soils

The minimum grade of elimination in the sewage plant is (%): 87.45

Water flow in sewage/river (m³/day): 18000

Number of the contributing scenario 2
Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 7
Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

Number of the contributing scenario 8
Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 0.014 mg/l; RCR: 0.165 |
| Fresh Water (Sediment) | PEC: 0.053 mg/kg dw; RCR: 0.165 |
| Marine Water (Pelagic) | PEC: 1.41E-3 mg/l; RCR: 0.172 |
| Marine Water (Sediment) | PEC: 5.57E-3 mg/kg dw; RCR: 0.172 |
| Agricultural Soil | PEC: 1.58E-3 mg/kg dw; RCR: 0.095 |
| Sewage Treatment Plant (Effluent) | PEC: 0.092 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. Exposure estimates are given for either short-term or long-term exposure depending on which lead to more conservative risk characterisation ratios.

| | |
|---------|------------------|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 15.44 |
| Proc 3 | EE(inhal): 30.88 |
| Proc 4 | EE(inhal): 61.77 |
| Proc 8a | EE(inhal): 15.44 |
| Proc 8b | EE(inhal): 3.861 |
| Proc 9 | EE(inhal): 15.44 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--------------------|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.05 |
| Proc 3 | RCR(inhal): 0.10 |
| Proc 4 | RCR(inhal): 0.199 |
| Proc 8a | RCR(inhal): 0.05 |
| Proc 8b | RCR(inhal): 0.012 |
| Proc 9 | RCR(inhal): 0.05 |

Number of the ES 2

Short title of the exposure scenario

Formulation & (re)packing of substances and mixtures

List of use descriptors

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU10: Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

Environmental release categories [ERC]

ERC2: Formulation of preparations (mixtures)

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

Further explanations

Industrial use

Assessment tool used:

Chesar 3.2

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently).

Assumes an advanced standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for ERC 2

Further specification

Specific Environmental Release Categories [SPERC], SpERC ESVOC 2.2.v1 (ESVOC 4), release factors for (Sp)ERC were modified.

Amounts used

Daily amount per site: 133 to

Annual amount per site: 40000 to

Other given operational conditions affecting environmental exposure

Indoor use

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 2.5E-3%

Release fraction to wastewater from process: 5E-7%

Release fraction to soil from process: 0.01%

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 95 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 99.9 % Upgrade of the system in place or additional air treatment measures, such as wet scrubber and/or air filtration and/or thermal oxidation and/or vapour recovery systems, in order to achieve a reduction of the air emissions.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

Water flow in sewage/river (m³/day): 18000

The minimum grade of elimination in the sewage plant is (%): 87.45

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Do not apply industrial sludge to natural soils

Number of the contributing scenario 2
Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 5

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 7

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 8

Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

Number of the contributing scenario 9

Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 10

Contributing exposure scenario controlling worker exposure for PROC 15

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|----------------------------------|
| Fresh Water (Pelagic) | PEC: 4.28E-3 mg/l; RCR: 0.052 |
| Fresh Water (Sediment) | PEC: 0.017 mg/kg dw; RCR: 0.052 |
| Marine Water (Pelagic) | PEC: 4.89E-4 mg/l; RCR: 0.06 |
| Marine Water (Sediment) | PEC: 1.93E-3 mg/kg dw; RCR: 0.06 |
| Agricultural Soil | PEC: 6.58E-4 mg/kg dw; RCR: 0.04 |
| Sewage Treatment Plant (Effluent) | PEC: 4.17E-5 mg/l; RCR: < 0.01 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|------------------|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 15.44 |
| Proc 3 | EE(inhal): 30.88 |
| Proc 4 | EE(inhal): 61.77 |
| Proc 5 | EE(inhal): 15.44 |
| Proc 8a | EE(inhal): 15.44 |
| Proc 8b | EE(inhal): 3.861 |
| Proc 9 | EE(inhal): 15.44 |
| Proc 15 | EE(inhal): 30.88 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--------------------|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.05 |
| Proc 3 | RCR(inhal): 0.1 |
| Proc 4 | RCR(inhal): 0.199 |
| Proc 5 | RCR(inhal): 0.05 |
| Proc 8a | RCR(inhal): 0.05 |
| Proc 8b | RCR(inhal): 0.012 |
| Proc 9 | RCR(inhal): 0.05 |
| Proc 15 | RCR(inhal): 0.1 |

Number of the ES 3

Short title of the exposure scenario

Distribution of substance

List of use descriptors

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

SU8: Manufacture of bulk, large scale chemicals (including petroleum products)

SU9: Manufacture of fine chemicals

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15: Use as laboratory reagent

Environmental release categories [ERC]

ERC2: Formulation of preparations (mixtures)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading, distribution and associated laboratory activities.

Further explanations

Industrial use

Assessment tool used:

Chesar 3.2

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes an advanced standard of occupational Health and Safety Management System

Contributing Scenarios

| | |
|--|----------|
| Number of the contributing scenario | 1 |
| Contributing exposure scenario controlling environmental exposure for ERC 2 | |

Further specification

Specific Environmental Release Categories [SPERC], SpERC ESVOC 1.1b.v1 (ESVOC 3), release factors for (Sp)ERC were modified.

Amounts used

Daily amount per site: 0.13 to

Annual amount per site: 197621 to

Fraction of EU tonnage used in region: 1

Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

Technical conditions and measures at process level (source) to prevent release

Release fraction to wastewater from process: 1E-3%

Release fraction to soil from process: 1E-3%

Release fraction to air from process: 0.01%

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Apply vapour recovery (Adsorption, ...). Assumed Efficiency: 90 % Typical measures to maintain workplace concentrations or airborne VOCs and particulates below respective OELS.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

Water flow in sewage/river (m³/day): 18000

The minimum grade of elimination in the sewage plant is (%): 87.45

| | |
|--|----------|
| Number of the contributing scenario | 2 |
| Contributing exposure scenario controlling worker exposure for PROC 1 | |

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

| | |
|--|----------|
| Number of the contributing scenario | 3 |
| Contributing exposure scenario controlling worker exposure for PROC 2 | |

Frequency and duration of use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

4 h (half shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 7
Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

4 h (half shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 8
Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

4 h (half shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 9
Contributing exposure scenario controlling worker exposure for PROC 15

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 4.29E-3 mg/l; RCR: 0.052 |
| Fresh Water (Sediment) | PEC: 0.017 mg/kg dw; RCR: 0.052 |
| Marine Water (Pelagic) | PEC: 4.89E-4 mg/l; RCR: 0.06 |
| Marine Water (Sediment) | PEC: 1.93E-3 mg/kg dw; RCR: 0.06 |
| Agricultural Soil | PEC: 2.22E-3 mg/kg dw; RCR: 0.133 |
| Sewage Treatment Plant (Effluent) | PEC: 8.27E-5 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|------------------|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 61.77 |
| Proc 3 | EE(inhal): 77.21 |
| Proc 4 | EE(inhal): 154.4 |
| Proc 8a | EE(inhal): 185.3 |
| Proc 8b | EE(inhal): 92.65 |
| Proc 9 | EE(inhal): 185.3 |
| Proc 15 | EE(inhal): 30.88 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--------------------|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.199 |
| Proc 3 | RCR(inhal): 0.249 |
| Proc 4 | RCR(inhal): 0.498 |
| Proc 8a | RCR(inhal): 0.598 |
| Proc 8b | RCR(inhal): 0.299 |
| Proc 9 | RCR(inhal): 0.598 |
| Proc 15 | RCR(inhal): 0.1 |

Number of the ES 4

Short title of the exposure scenario

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Uses in coatings

List of use descriptors

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

PROC15: Use as laboratory reagent

Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Covers the use in coatings (paints, inks, adhesives, etc) within closed or contained systems including incidental exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application activities and film formation) and equipment cleaning, maintenance and associated laboratory activities.

Further explanations

Industrial use

Assessment tool used:

Chesar 3.2

StoffenManager V 6 for Following PROC:

PROC 7

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes an advanced standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for
ERC 4

Further specification

release factors for (Sp)ERC were modified.

Amounts used

Daily amount per site: 46.0 to

Annual amount per site: 13804 to

Fraction of EU tonnage used in region: 1

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0.18 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Release fraction to wastewater from process: 0 %

Release fraction to soil from process: 0%

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air; Apply air filtration - particle removal. Assumed Efficiency: 95 %

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

Water flow in sewage/river (m³/day): 18000

The minimum grade of elimination in the sewage plant is (%): 87.45

Do not apply industrial sludge to natural soils

Number of the contributing scenario 2
Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 1 hand (240 cm²)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario

7

Contributing exposure scenario controlling worker exposure for PROC 7

Further specification

Assessment tool used: StoffenManager

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario

8

Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario

9

Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

Number of the contributing scenario

10

Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 11
Contributing exposure scenario controlling worker exposure for PROC 10

Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 12
Contributing exposure scenario controlling worker exposure for PROC 13

Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 13
Contributing exposure scenario controlling worker exposure for PROC 15

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 4.28E-3 mg/l; RCR: 0.052 |
| Fresh Water (Sediment) | PEC: 0.017 mg/kg dw; RCR: 0.052 |
| Marine Water (Pelagic) | PEC: 4.88E-4 mg/l; RCR: 0.06 |
| Marine Water (Sediment) | PEC: 1.93E-3 mg/kg dw; RCR: 0.059 |
| Agricultural Soil | PEC: 2.64E-3 mg/kg dw; RCR: 0.159 |
| Sewage Treatment Plant (Effluent) | PEC: 0 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|------------------|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 15.44 |
| Proc 3 | EE(inhal): 30.88 |
| Proc 4 | EE(inhal): 61.77 |
| Proc 5 | EE(inhal): 15.44 |
| Proc 7 | EE(inhal): 0 |
| Proc 8a | EE(inhal): 15.44 |
| Proc 8b | EE(inhal): 3.861 |
| Proc 9 | EE(inhal): 15.44 |
| Proc 10 | EE(inhal): 15.44 |
| Proc 13 | EE(inhal): 15.44 |
| Proc 15 | EE(inhal): 30.88 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--------------------|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.05 |
| Proc 3 | RCR(inhal): 0.1 |
| Proc 4 | RCR(inhal): 0.199 |
| Proc 5 | RCR(inhal): 0.05 |
| Proc 7 | RCR(inhal): < 0.01 |
| Proc 8a | RCR(inhal): 0.05 |
| Proc 8b | RCR(inhal): 0.012 |
| Proc 9 | RCR(inhal): 0.05 |
| Proc 10 | RCR(inhal): 0.05 |
| Proc 13 | RCR(inhal): 0.05 |
| Proc 15 | RCR(inhal): 0.1 |

Number of the ES 5

Short title of the exposure scenario

Uses in coatings

List of use descriptors

Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

PROC11: Non industrial spraying
PROC13: Treatment of articles by dipping and pouring
PROC15: Use as laboratory reagent
PROC19: Hand-mixing with intimate contact and only PPE available

Environmental release categories [ERC]

ERC8d: Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Covers the use in coatings (paints, inks, adhesives, etc) within closed or contained systems including incidental exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application activities and film formation) and equipment cleaning, maintenance and associated laboratory activities.

Further explanations

Professional use

Assessment tool used:

Chesar 3.2

StoffenManager V 6 for Following PROC:

PROC 11

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes a basic standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for ERC 8d

Further specification

Specific Environmental Release Categories [SPERC], SpERC ESVOC 8.3b.v1.

Amounts used

daily wide dispersive use: 0.0042 to/d

Fraction of Regional tonnage used locally: 0.0005

Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 98 %

Release fraction to wastewater from process: 1 %

Release fraction to soil from process: 1%

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.45

Conditions and measures related to external treatment of waste for disposal

Dispose of waste product or used containers according to local regulations

Number of the contributing scenario

2

Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 5

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Number of the contributing scenario 7
Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 8
Contributing exposure scenario controlling worker exposure for PROC 8b

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 9

Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 10

Contributing exposure scenario controlling worker exposure for PROC 10

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 11

Contributing exposure scenario controlling worker exposure for PROC 11

Further specification

Assessment tool used: StoffenManager

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 12

Contributing exposure scenario controlling worker exposure for PROC 11

Further specification

Assessment tool used: StoffenManager

Frequency and duration of use

Exposure time per day: 6 h/d

Other given operational conditions affecting workers exposure

Indoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Room volume 100 - 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.

Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 13
Contributing exposure scenario controlling worker exposure for PROC 11

Further specification

Assessment tool used: StoffenManager

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume < 100 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.

Technical conditions and measures to control dispersion from source towards the worker

Provide enhanced general ventilation by mechanical means. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 80 %) Alternatively: Use duration max. 5 h. Inspect and clean equipment regularly.

Number of the contributing scenario 14
Contributing exposure scenario controlling worker exposure for PROC 13

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 15
Contributing exposure scenario controlling worker exposure for PROC 15

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 16
Contributing exposure scenario controlling worker exposure for PROC 19

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 4.54E-3 mg/l; RCR: 0.055 |
| Fresh Water (Sediment) | PEC: 0.018 mg/kg dw; RCR: 0.055 |
| Marine Water (Pelagic) | PEC: 5.15E-4 mg/l; RCR: 0.063 |
| Marine Water (Sediment) | PEC: 2.03E-3 mg/kg dw; RCR: 0.063 |
| Agricultural Soil | PEC: 5.92E-4 mg/kg dw; RCR: 0.036 |
| Sewage Treatment Plant (Effluent) | PEC: 2.66E-3 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|---|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 61.77 |
| Proc 3 | EE(inhal): 77.21 |
| Proc 4 | EE(inhal): 154.4 |
| Proc 5 | EE(inhal): 185.3 |
| Proc 8a | EE(inhal): 185.3 |
| Proc 8b | EE(inhal): 92.65 |
| Proc 9 | EE(inhal): 185.3 |
| Proc 10 | EE(inhal): 185.3 |
| Proc 11 | EE(inhal): 0 - Contributing Scenario 11 EE(inhal): 300 - Contributing Scenario 12 EE(inhal): 187.5 - Contributing Scenario 13 |
| Proc 13 | EE(inhal): 185.3 |
| Proc 15 | EE(inhal): 30.88 |
| Proc 19 | EE(inhal): 185.3 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.199 |
| Proc 3 | RCR(inhal): 0.249 |
| Proc 4 | RCR(inhal): 0.498 |
| Proc 5 | RCR(inhal): 0.598 |
| Proc 8a | RCR(inhal): 0.598 |
| Proc 8b | RCR(inhal): 0.299 |
| Proc 9 | RCR(inhal): 0.598 |
| Proc 10 | RCR(inhal): 0.598 |
| Proc 11 | RCR(inhal): < 0.01 - Contributing Scenarios 11 RCR(inhal): 0.968 - Contributing Scenarios 12 RCR(inhal): 0.605 - Contributing Scenarios 13 |
| Proc 13 | RCR(inhal): 0.598 |
| Proc 15 | RCR(inhal): 0.1 |
| Proc 19 | RCR(inhal): 0.598 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Number of the ES 6

Short title of the exposure scenario

Use in Cleaning Products

List of use descriptors

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Covers the use as a component of cleaning products including transfer from storage, pouring/unloading from drums or containers. exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand), related equipment cleaning and maintenance.

Further explanations

Industrial use

Assessment tool used:

Chesar 3.2

StoffenManager V 6 for Following PROC:

PROC 7

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently).

Assumes an advanced standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for ERC 4

Further specification

SpERC ESVOC 4.4a.v1 (ESVOC 8), Specific Environmental Release Categories [SPERC], release factors for (Sp)ERC were modified.

Amounts used

Daily amount per site: 106.8 to

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Annual amount per site: 2136 to

Other given operational conditions affecting environmental exposure

Indoor use

Technical conditions and measures at process level (source) to prevent release

Release fraction to wastewater from process: 3E-3%

Release fraction to soil from process: 0%

Release fraction to air from process: 0.1%

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 99.9 % Typical measures to maintain workplace concentrations of airborne VOCs and particulates below respective OELs: e.g. thermal wet scrubber, gas removal and/or air filtration, particle removal and/or thermal oxidation and/or vapour recovery, adsorption. Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 70 %

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

Water flow in sewage/river (m³/day): 18000

The minimum grade of elimination in the sewage plant is (%): 87.45

Number of the contributing scenario 2
Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 7

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 7
Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 8
Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

Number of the contributing scenario 9
Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 10
Contributing exposure scenario controlling worker exposure for PROC 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario

11

Contributing exposure scenario controlling worker exposure for PROC 13

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 0.024 mg/l; RCR: 0.297 |
| Fresh Water (Sediment) | PEC: 0.096 mg/kg dw; RCR: 0.297 |
| Marine Water (Pelagic) | PEC: 2.5E-3 mg/l; RCR: 0.305 |
| Marine Water (Sediment) | PEC: 9.87E-3 mg/kg dw; RCR: 0.304 |
| Agricultural Soil | PEC: 7.52E-4 mg/kg dw; RCR: 0.045 |
| Sewage Treatment Plant (Effluent) | PEC: < 0.01 mg/l; RCR: 0.0001 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|------------------|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 15.44 |
| Proc 3 | EE(inhal): 30.88 |
| Proc 4 | EE(inhal): 61.77 |
| Proc 7 | EE(inhal): 0 |
| Proc 8a | EE(inhal): 15.44 |
| Proc 8b | EE(inhal): 3.861 |
| Proc 9 | EE(inhal): 15.44 |
| Proc 10 | EE(inhal): 15.44 |
| Proc 13 | EE(inhal): 15.44 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--------------------|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.05 |
| Proc 3 | RCR(inhal): 0.1 |
| Proc 4 | RCR(inhal): 0.199 |
| Proc 7 | RCR(inhal): < 0.01 |
| Proc 8a | RCR(inhal): 0.05 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

| | |
|---------|-------------------|
| Proc 8b | RCR(inhal): 0.012 |
| Proc 9 | RCR(inhal): 0.05 |
| Proc 10 | RCR(inhal): 0.05 |
| Proc 13 | RCR(inhal): 0.05 |

Number of the ES 7

Short title of the exposure scenario

Use in Cleaning Products

List of use descriptors

Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

Environmental release categories [ERC]

ERC8d: Wide dispersive outdoor use of processing aids in open systems

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Covers the use as a component of cleaning products including pouring/unloading from drums or containers; and exposures during mixing/diluting in the preparatory phase and cleaning activities (including spraying, brushing, dipping, wiping, automated and by hand).

Further explanations

Professional use

Assessment tool used:

Chesar 3.2

StoffenManager V 6 for Following PROC:

PROC 11

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes a basic standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for ERC 8d

Further specification

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Specific Environmental Release Categories [SPERC], SpERC ESVOC 8.4b.v1 (ESVOC 9).

Amounts used

daily wide dispersive use: 0.0004 to/d

Frequency and duration of use

Covers use up to: 365 days

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 98%

Release fraction to wastewater from process: 1%

Release fraction to soil from process: 1%

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.45

Number of the contributing scenario 2
Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

PROC 8a

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 7

Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 8

Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 9

Contributing exposure scenario controlling worker exposure for PROC 10

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 10

Contributing exposure scenario controlling worker exposure for PROC 11

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Number of the contributing scenario 11
Contributing exposure scenario controlling worker exposure for PROC 11

Frequency and duration of use

Exposure time per day: 6 h/d

Other given operational conditions affecting workers exposure

Indoor use

Room volume 100 - 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 12
Contributing exposure scenario controlling worker exposure for PROC 11

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume < 100 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.

Technical conditions and measures to control dispersion from source towards the worker

Provide enhanced general ventilation by mechanical means. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 80 %) Alternatively: Use duration max. 5 h. Inspect and clean equipment regularly.

Number of the contributing scenario 13
Contributing exposure scenario controlling worker exposure for PROC 13

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 4.3E-3 mg/l; RCR: 0.052 |
| Fresh Water (Sediment) | PEC: 0.017 mg/kg dw; RCR: 0.052 |
| Marine Water (Pelagic) | PEC: 4.91E-4 mg/l; RCR: 0.06 |
| Marine Water (Sediment) | PEC: 1.94E-3 mg/kg dw; RCR: 0.06 |
| Agricultural Soil | PEC: 5.77E-4 mg/kg dw; RCR: 0.035 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Sewage Treatment Plant
(Effluent) PEC: 2.49E-4 mg/l; RCR: < 0.01

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|---|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 61.75 |
| Proc 3 | EE(inhal): 77.21 |
| Proc 4 | EE(inhal): 154.4 |
| Proc 8a | EE(inhal): 185.3 |
| Proc 8b | EE(inhal): 92.65 |
| Proc 9 | EE(inhal): 185.3 |
| Proc 10 | EE(inhal): 185.3 |
| Proc 11 | EE(inhal): 0 - Contributing Scenario 10 EE(inhal): 300 - Contributing Scenario 11 EE(inhal): 187.5 - Contributing Scenario 12 |
| Proc 13 | EE(inhal): 185.3 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|---|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.199 |
| Proc 3 | RCR(inhal): 0.249 |
| Proc 4 | RCR(inhal): 0.498 |
| Proc 8a | RCR(inhal): 0.598 |
| Proc 8b | RCR(inhal): 0.299 |
| Proc 9 | RCR(inhal): 0.598 |
| Proc 10 | RCR(inhal): 0.598 |
| Proc 11 | RCR(inhal): 0 - Contributing Scenarios 10 RCR(inhal): 0.968 - Contributing Scenarios 11 RCR(inhal): 0.605 - Contributing Scenarios 12 |
| Proc 13 | RCR(inhal): 0.598 |

Number of the ES 8

Short title of the exposure scenario

Lubricants

List of use descriptors

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC10: Roller application or brushing
PROC13: Treatment of articles by dipping and pouring
PROC17: Lubrication at high energy conditions and in partly open process
PROC18: Greasing at high energy conditions

Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of machinery/engines and similar articles, reworking on reject articles, equipment maintenance and disposal of wastes.

Further explanations

Industrial use

Assessment tool used:

Chesar 3.2

StoffenManager V 6 for Following PROC:

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes an advanced standard of occupational Health and Safety Management System

Contributing Scenarios

| | |
|--|----------|
| Number of the contributing scenario | 1 |
| Contributing exposure scenario controlling environmental exposure for ERC 4 | |

Further specification

release factors for (Sp)ERC were modified, A&B Tables: A3.8, B3.7.

Amounts used

Daily amount per site: 1.45 to

Annual amount per site: 506 to

Fraction of EU tonnage used in region: 1

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 0.5 %

Release fraction to wastewater from process: 0.05 %

Release fraction to soil from process: 0.1%

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

Water flow in sewage/river (m³/day): 18000

The minimum grade of elimination in the sewage plant is (%): 87.45

| | |
|--|----------|
| Number of the contributing scenario | 2 |
| Contributing exposure scenario controlling worker exposure for PROC 1 | |

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

| | |
|--|----------|
| Number of the contributing scenario | 3 |
|--|----------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 7

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Room volume > 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 7
Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 8
Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

Number of the contributing scenario 9
Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 10
Contributing exposure scenario controlling worker exposure for PROC 10

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 11
Contributing exposure scenario controlling worker exposure for PROC 13

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 12
Contributing exposure scenario controlling worker exposure for PROC 17

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Technical conditions and measures to control dispersion from source towards the worker
provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 13
Contributing exposure scenario controlling worker exposure for PROC 17

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 14
Contributing exposure scenario controlling worker exposure for PROC 18

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 15
Contributing exposure scenario controlling worker exposure for PROC 18

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 8.82E-3 mg/l; RCR: 0.107 |
| Fresh Water (Sediment) | PEC: 0.035 mg/kg dw; RCR: 0.107 |
| Marine Water (Pelagic) | PEC: 9.42E-4 mg/l; RCR: 0.115 |
| Marine Water (Sediment) | PEC: 3.72E-3 mg/kg dw; RCR: 0.115 |
| Agricultural Soil | PEC: 1.06E-3 mg/kg dw; RCR: 0.064 |
| Sewage Treatment Plant (Effluent) | PEC: 0.045 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|--------|------------------|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 15.44 |
| Proc 3 | EE(inhal): 30.88 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

| | |
|---------|--|
| Proc 4 | EE(inhal): 61.77 |
| Proc 7 | EE(inhal): 0 |
| Proc 8a | EE(inhal): 15.44 |
| Proc 8b | EE(inhal): 3.861 |
| Proc 9 | EE(inhal): 15.44 |
| Proc 10 | EE(inhal): 15.44 |
| Proc 13 | EE(inhal): 15.44 |
| Proc 17 | EE(inhal): 154.4 - Contributing Scenario 12 EE(inhal): 30.88 - Contributing Scenario 13 |
| Proc 18 | EE(inhal): 154.4 - Contributing Scenario 14 EE(inhal): 30.88 - Contributing Scenario 15 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.05 |
| Proc 3 | RCR(inhal): 0.1 |
| Proc 4 | RCR(inhal): 0.199 |
| Proc 7 | RCR(inhal): < 0.01 |
| Proc 8a | RCR(inhal): 0.05 |
| Proc 8b | RCR(inhal): 0.012 |
| Proc 9 | RCR(inhal): 0.05 |
| Proc 10 | RCR(inhal): 0.05 |
| Proc 13 | RCR(inhal): 0.05 |
| Proc 17 | RCR(inhal): 0.498 - Contributing Scenarios 12 RCR(inhal): 0.1 - Contributing Scenarios 13 |
| Proc 18 | RCR(inhal): 0.498 - Contributing Scenarios 14 RCR(inhal): 0.1 - Contributing Scenarios 15 |

Number of the ES 9

Short title of the exposure scenario

Lubricants

List of use descriptors

Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC17: Lubrication at high energy conditions and in partly open process

PROC18: Greasing at high energy conditions

PROC20: Heat and pressure transfer fluids in dispersive, professional use but closed systems

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Environmental release categories [ERC]

ERC9b: Wide dispersive outdoor use of substances in closed systems

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Covers the use of formulated lubricants in closed and open systems including transfer operations, operation of engines and similar articles, reworking on reject articles, equipment maintenance and disposal of waste oil.

Further explanations

Professional use

Assessment tool used:

Chesar 3.2

StoffenManager V 6 for Following PROC:

PROC 11

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes a basic standard of occupational Health and Safety Management System

Contributing Scenarios

| | |
|---|----------|
| Number of the contributing scenario | 1 |
| Contributing exposure scenario controlling environmental exposure for ERC 9b | |

Further specification

Specific Environmental Release Categories [SPERC], SpERC ESVOC 9.6b.v1 (ESVOC 14), SpERC ESVOC 9.6d.v1 (ESVOC 16).

Amounts used

daily wide dispersive use: 0.000051 to/d

Fraction of EU tonnage used in region: 0.0000512

Fraction of Regional tonnage used locally: 0.0000513

Frequency and duration of use

Covers use up to: 365 days

Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from wide dispersive use (regional only): 1 %

Release fraction to wastewater from wide dispersive use: 1 %

Release fraction to soil from wide dispersive use (regional only): 1%

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.45

| | |
|--|----------|
| Number of the contributing scenario | 2 |
| Contributing exposure scenario controlling worker exposure for PROC 1 | |

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

| | |
|--|----------|
| Number of the contributing scenario | 3 |
|--|----------|

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4

Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5

Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6

Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 7

Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 8

Contributing exposure scenario controlling worker exposure for PROC 9

Other given operational conditions affecting workers exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker
provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 9
Contributing exposure scenario controlling worker exposure for PROC 10

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker
provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 10
Contributing exposure scenario controlling worker exposure for PROC 11

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 11
Contributing exposure scenario controlling worker exposure for PROC 11

Frequency and duration of use

Exposure time per day: 6 h/d

Other given operational conditions affecting workers exposure

Indoor use

Room volume 100 - 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.

Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 12
Contributing exposure scenario controlling worker exposure for PROC 11

Product characteristics

Liquid, vapour pressure 0,5 - 10 kPa at STP

Covers percentage substance in the product up to 100 % (unless stated differently)

Frequency and duration of use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume < 100 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.

Technical conditions and measures to control dispersion from source towards the worker

Provide enhanced general ventilation by mechanical means. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly. Wear respiratory protection (Efficiency: 80 %) Alternatively: Use duration max. 5 h.

Number of the contributing scenario

13

Contributing exposure scenario controlling worker exposure for PROC 13

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario

14

Contributing exposure scenario controlling worker exposure for PROC 17

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 90 %) Alternatively: Use duration max. 1 h.

Number of the contributing scenario

15

Contributing exposure scenario controlling worker exposure for PROC 17

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor use

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative).

Conditions and measures related to personal protection, hygiene and health evaluation

If above technical/organisational control measures are not feasible, then adopt following PPE. If carried out for more than 1h, wear respiratory protection (efficiency 90%).

Number of the contributing scenario

16

Contributing exposure scenario controlling worker exposure for PROC 18

Frequency and duration of use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative). If no adequate ventilation is available, avoid carrying out operations for more than 1 h.

Number of the contributing scenario

17

Contributing exposure scenario controlling worker exposure for PROC 18

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor use

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative).

Conditions and measures related to personal protection, hygiene and health evaluation

If above technical/organisational control measures are not feasible, then adopt following PPE. If carried out for more than 1h, wear respiratory protection (efficiency 90%).

Number of the contributing scenario

18

Contributing exposure scenario controlling worker exposure for PROC 20

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 4.28E-3 mg/l; RCR: 0.052 |
| Fresh Water (Sediment) | PEC: 0.017 mg/kg dw; RCR: 0.052 |
| Marine Water (Pelagic) | PEC: 4.88E-4 mg/l; RCR: 0.06 |
| Marine Water (Sediment) | PEC: 1.93E-3 mg/kg dw; RCR: 0.06 |
| Agricultural Soil | PEC: 5.76E-4 mg/kg dw; RCR: 0.035 |
| Sewage Treatment Plant (Effluent) | PEC: 3.21E-5 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|------------------|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 61.77 |
| Proc 3 | EE(inhal): 77.21 |
| Proc 4 | EE(inhal): 154.4 |
| Proc 8a | EE(inhal): 185.3 |
| Proc 8b | EE(inhal): 92.65 |
| Proc 9 | EE(inhal): 185.3 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

| | |
|---------|--|
| Proc 10 | EE(inhal): 185.3 |
| Proc 11 | EE(inhal): 0 - Contributing Scenario 10 EE(inhal): 300 - Contributing Scenario 11 EE(inhal): 187.50 - Contributing Scenario 12 |
| Proc 13 | EE(inhal): 185.3 |
| Proc 17 | EE(inhal): 185.3 - Contributing Scenario 14 EE(inhal): 123.5 - Contributing Scenario 15 |
| Proc 18 | EE(inhal): 123.5 - Contributing Scenario 16 EE(inhal): 185.3 - Contributing Scenario 17 |
| Proc 20 | EE(inhal): 61.77 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.199 |
| Proc 3 | RCR(inhal): 0.249 |
| Proc 4 | RCR(inhal): 0.498 |
| Proc 8a | RCR(inhal): 0.598 |
| Proc 8b | RCR(inhal): 0.299 |
| Proc 9 | RCR(inhal): 0.598 |
| Proc 10 | RCR(inhal): 0.598 |
| Proc 11 | RCR(inhal): < 0.01 - Contributing Scenarios 10 RCR(inhal): 0.968 - Contributing Scenarios 11 RCR(inhal): 0.605 - Contributing Scenarios 12 |
| Proc 13 | RCR(inhal): 0.598 |
| Proc 17 | RCR(inhal): 0.598 - Contributing Scenarios 14 RCR(inhal): 0.399 - Contributing Scenarios 15 |
| Proc 18 | RCR(inhal): 0.399 - Contributing Scenarios 16 RCR(inhal): 0.598 - Contributing Scenarios 17 |
| Proc 20 | RCR(inhal): 0.199 |

Number of the ES 10

Short title of the exposure scenario

Metal working fluids / rolling oils

List of use descriptors

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC7: Industrial spraying

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC10: Roller application or brushing

PROC13: Treatment of articles by dipping and pouring

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

PROC17: Lubrication at high energy conditions and in partly open process

Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Covers the use in formulated MWFs (MWFs) including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.

Further explanations

Industrial use

Assessment tool used:

Chesar 3.2

StoffenManager V 6 for Following PROC:

PROC 7

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes an advanced standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for ERC 4

Further specification

Specific Environmental Release Categories [SPERC], SpERC ESVOC 4.7a.v1 (ESVOC 18), release factors for (Sp)ERC were modified.

Amounts used

Daily amount per site: 2 to

Annual amount per site: 40 to

Fraction of EU tonnage used in region: 1

Technical conditions and measures at process level (source) to prevent release

Release fraction to wastewater from process: 0.03 %

Release fraction to soil from process: 0%

Release fraction to air from process: 0.6 %

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 70 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 70 %

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.45

Water flow in sewage/river (m³/day): 18000

Conditions and measures related to external treatment of waste for disposal

Dispose of waste product or used containers according to local regulations

Number of the contributing scenario

2

Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 5

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 7

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 7
Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 9

Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

8 h (full shift)

Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm²)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

Number of the contributing scenario 10

Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 11

Contributing exposure scenario controlling worker exposure for PROC 10

Frequency and duration of use

8 h (full shift)

Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm²)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario 12

Contributing exposure scenario controlling worker exposure for PROC 13

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Number of the contributing scenario 13
Contributing exposure scenario controlling worker exposure for PROC 17

Frequency and duration of use

8 h (full shift)

Human factors not influenced by risk management

Area potentially exposed: corresponds to 2 hands (960 cm²)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 14
Contributing exposure scenario controlling worker exposure for PROC 17

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 95 %).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 8.04E-3 mg/l; RCR: 0.098 |
| Fresh Water (Sediment) | PEC: 0.032 mg/kg dw; RCR: 0.098 |
| Marine Water (Pelagic) | PEC: 8.65E-4 mg/l; RCR: 0.106 |
| Marine Water (Sediment) | PEC: 3.41E-3 mg/kg dw; RCR: 0.105 |
| Agricultural Soil | PEC: 8.25E-4 mg/kg dw; RCR: 0.05 |
| Sewage Treatment Plant (Effluent) | PEC: 0.038 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|---|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 15.44 |
| Proc 3 | EE(inhal): 30.88 |
| Proc 5 | EE(inhal): 15.44 |
| Proc 7 | EE(inhal): 0 |
| Proc 8a | EE(inhal): 15.44 |
| Proc 8b | EE(inhal): 3.861 |
| Proc 9 | EE(inhal): 15.44 |
| Proc 10 | EE(inhal): 15.44 |
| Proc 13 | EE(inhal): 15.44 |
| Proc 17 | EE(inhal): 154.38 - Contributing Scenario 13 EE(inhal): 15.44 - Contributing Scenario 14 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

calculated values.

| | |
|---------|---|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.05 |
| Proc 3 | RCR(inhal): 0.1 |
| Proc 5 | RCR(inhal): 0.05 |
| Proc 7 | RCR(inhal): < 0.01 |
| Proc 8a | RCR(inhal): 0.05 |
| Proc 8b | RCR(inhal): 0.012 |
| Proc 9 | RCR(inhal): 0.05 |
| Proc 10 | RCR(inhal): 0.05 |
| Proc 13 | RCR(inhal): 0.05 |
| Proc 17 | RCR(inhal): 0.498 - Contributing Scenarios 13 RCR(inhal): 0.05 - Contributing Scenarios 14 |

Number of the ES 11

Short title of the exposure scenario

Metal working fluids / rolling oils

List of use descriptors

Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC10: Roller application or brushing

PROC11: Non industrial spraying

PROC13: Treatment of articles by dipping and pouring

PROC17: Lubrication at high energy conditions and in partly open process

Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Covers the use in formulated MWFs (MWFs) including transfer operations, open and contained cutting/machining activities, automated and manual application of corrosion protections, draining and working on contaminated/ reject articles, and disposal of waste oils.

Further explanations

Professional use

Chesar 3.2

Assessment tool used:

StoffenManager V 6 for Following PROC:

PROC 11

liquid

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Assumes use at not more than 20°C above ambient temperature (unless stated differently)
Covers percentage substance in the product up to 100 % (unless stated differently).
Assumes a basic standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario 1
Contributing exposure scenario controlling environmental exposure for ERC 8a

Further specification

Specific Environmental Release Categories [SPERC], SpERC ESVOC 8.7c.v1 (ESVOC 20).

Amounts used

daily wide dispersive use: 0.055 t/d

Fraction of Regional tonnage used locally: 0.0005

Frequency and duration of use

Covers use up to: 365 days

Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from wide dispersive use (regional only): 40%

Release fraction to wastewater from wide dispersive use: 5%

Release fraction to soil from wide dispersive use (regional only): 5%

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.45

Number of the contributing scenario 2
Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 5

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 7
Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 8
Contributing exposure scenario controlling worker exposure for PROC 10

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 9
Contributing exposure scenario controlling worker exposure for PROC 11

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume > 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Technical conditions and measures to control dispersion from source towards the worker

Use in ventilated spray booths only.

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 10
Contributing exposure scenario controlling worker exposure for PROC 11

Frequency and duration of use

Exposure time per day: 6 h/d

Other given operational conditions affecting workers exposure

Indoor use

Room volume 100 - 1000 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.

Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly.

Number of the contributing scenario 11
Contributing exposure scenario controlling worker exposure for PROC 11

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Room volume < 100 m³

Ensure that the task is being carried out outside the breathing zone of a worker (distance head-product greater than 1m).

Ensure that the task is not carried out by more than one worker simultaneously.

Technical conditions and measures to control dispersion from source towards the worker

Provide enhanced general ventilation by mechanical means. Effectiveness of LEV (local exhaust ventilation): 47 % (inhalative).

Organisational measures to prevent /limit releases, dispersion and exposure

Clean equipment and the work area every day

Ensure the ventilation system is regularly maintained and tested

Conditions and measures related to personal protection, hygiene and health evaluation

Inspect and clean equipment regularly. Wear respiratory protection (Efficiency: 80 %) Alternatively: Use duration max. 5 h.

Number of the contributing scenario 12
Contributing exposure scenario controlling worker exposure for PROC 13

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Human factors not influenced by risk management

Area potentially exposed: corresponds to palm of 2 hands (480 cm²)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 13
Contributing exposure scenario controlling worker exposure for PROC 17

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Wear respiratory protection (Efficiency: 90 %) Alternatively: Use duration max. 1 h.

Number of the contributing scenario

14

Contributing exposure scenario controlling worker exposure for PROC 17

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

Provide extract ventilation to points where emissions occur. Effectiveness of LEV (local exhaust ventilation): 80 % (inhalative).

Conditions and measures related to personal protection, hygiene and health evaluation

If above technical/organisational control measures are not feasible, then adopt following PPE. If carried out for more than 1h, wear respiratory protection (efficiency 90%).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 0.022 mg/l; RCR: 0.263 |
| Fresh Water (Sediment) | PEC: 0.085 mg/kg dw; RCR: 0.262 |
| Marine Water (Pelagic) | PEC: 2.21E-3 mg/l; RCR: 0.27 |
| Marine Water (Sediment) | PEC: 8.74E-3 mg/kg dw; RCR: 0.27 |
| Agricultural Soil | PEC: 1.63E-3 mg/kg dw; RCR: 0.098 |
| Sewage Treatment Plant (Effluent) | PEC: 0.173 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|---|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 61.77 |
| Proc 3 | EE(inhal): 77.21 |
| Proc 5 | EE(inhal): 185.3 |
| Proc 8a | EE(inhal): 185.3 |
| Proc 8b | EE(inhal): 92.65 |
| Proc 10 | EE(inhal): 185.3 |
| Proc 11 | EE(inhal): 0 - Contributing Scenario 9 |
| | EE(inhal): 300 - Contributing Scenario 10 |
| | EE(inhal): 187.4 - Contributing Scenario 11 |
| Proc 13 | EE(inhal): 185.3 |
| Proc 17 | EE(inhal): 123.5 - Contributing Scenario 13 |
| | EE(inhal): 185.3 - Contributing Scenario 14 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

| | |
|---------|---|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.199 |
| Proc 3 | RCR(inhal): 0.249 |
| Proc 5 | RCR(inhal): 0.598 |
| Proc 8a | RCR(inhal): 0.598 |
| Proc 8b | RCR(inhal): 0.299 |
| Proc 10 | RCR(inhal): 0.598 |
| Proc 11 | RCR(inhal): < 0.01 - Contributing Scenarios 9 RCR(inhal): 0.968 - Contributing Scenarios 10 RCR(inhal): 0.605 - Contributing Scenarios 11 |
| Proc 13 | RCR(inhal): 0.598 |
| Proc 17 | RCR(inhal): 0.399 - Contributing Scenarios 13 RCR(inhal): 0.598 - Contributing Scenarios 14 |

Number of the ES 12

Short title of the exposure scenario

Use in laboratories

List of use descriptors

Sector of uses [SU]

SU22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC10: Roller application or brushing
PROC15: Use as laboratory reagent

Environmental release categories [ERC]

ERC8a: Wide dispersive indoor use of processing aids in open systems

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Use of small quantities within laboratory settings, including material transfers and equipment cleaning

Further explanations

Professional use

Assessment tool used:

Chesar 3.2

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes a basic standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for ERC 8a

Further specification

Specific Environmental Release Categories [SPERC], SpERC ESVOC 8.17.v1 (ESVOC 39).

Amounts used

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

daily wide dispersive use: 0.0000088 to/d
Fraction of Regional tonnage used locally: 0.00000883

Frequency and duration of use

Covers use up to: 365 days

Other given operational conditions affecting environmental exposure

Indoor/Outdoor use

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 50 %

Release fraction to wastewater from process: 50 %

Release fraction to soil from process: 0%

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000

The minimum grade of elimination in the sewage plant is (%): 87.45

Number of the contributing scenario 2

Contributing exposure scenario controlling worker exposure for PROC 10

Frequency and duration of use

Avoid carrying out activities involving exposure for more than 4 hours

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3

Contributing exposure scenario controlling worker exposure for PROC 15

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 4.31E-3 mg/l; RCR: 0.053 |
| Fresh Water (Sediment) | PEC: 0.017 mg/kg dw; RCR: 0.052 |
| Marine Water (Pelagic) | PEC: 4.91E-4 mg/l; RCR: 0.06 |
| Marine Water (Sediment) | PEC: 1.94E-3 mg/kg dw; RCR: 0.06 |
| Agricultural Soil | PEC: 5.77E-4 mg/kg dw; RCR: 0.035 |
| Sewage Treatment Plant (Effluent) | PEC: 2.76E-4 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|------------------|
| Proc 10 | EE(inhal): 185.3 |
| Proc 15 | EE(inhal): 30.88 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

calculated values.

| | |
|---------|-------------------|
| Proc 10 | RCR(inhal): 0.598 |
| Proc 15 | RCR(inhal): 0.1 |

Number of the ES 13

Short title of the exposure scenario

Polymer processing

List of use descriptors

Sector of uses [SU]

SU3: Industrial uses: Uses of substances as such or in preparations at industrial sites

Process categories [PROC]

PROC1: Use in closed process, no likelihood of exposure

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

Environmental release categories [ERC]

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Product characteristics

Refer to attached safety data sheets

Processes and activities covered by the exposure scenario

Processing of formulated polymers including material transfers, moulding and forming activities, material re-works and associated maintenance

Further explanations

Industrial use

Assessment tool used:

Chesar 3.2

liquid

Assumes use at not more than 20°C above ambient temperature (unless stated differently)

Covers percentage substance in the product up to 100 % (unless stated differently)

Assumes an advanced standard of occupational Health and Safety Management System

Contributing Scenarios

Number of the contributing scenario

1

Contributing exposure scenario controlling environmental exposure for ERC 4

Further specification

Specific Environmental Release Categories [SPERC], SpERC ESVOC 4.21a.v1 (ESVOC 44).

Amounts used

Daily amount per site: 2 to

Annual amount per site: 600 to

Fraction of EU tonnage used in region: 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Technical conditions and measures at process level (source) to prevent release

Release fraction to air from process: 5 %
Release fraction to wastewater from process: 0 %
Release fraction to soil from process: 0.001%

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Onsite treatment off-air. Upgrade Systems in place or implement additional treatment. Assumed Efficiency: 80 % Onsite treatment wastewater. Apply acclimated biological treatment. Assumed Efficiency: 70 % Typical measures to maintain workplace concentrations of airborne VOCs and particulates below respective OELs: e.g. thermal wet scrubber, gas removal and/or air filtration, particle removal and/or thermal oxidation and/or vapour recovery, adsorption.

Conditions and measures related to municipal sewage treatment plant

Size of municipal sewage system/ treatment plant (m³/d): 2000
The minimum grade of elimination in the sewage plant is (%): 87.45

Number of the contributing scenario 2
Contributing exposure scenario controlling worker exposure for PROC 1

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 3
Contributing exposure scenario controlling worker exposure for PROC 2

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 4
Contributing exposure scenario controlling worker exposure for PROC 3

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 5
Contributing exposure scenario controlling worker exposure for PROC 4

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor and outdoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour).

Number of the contributing scenario 6
Contributing exposure scenario controlling worker exposure for PROC 8a

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Number of the contributing scenario

7

Contributing exposure scenario controlling worker exposure for PROC 8b

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

provide a basic standard of general ventilation (1 to 3 air changes per hour). Effectiveness of LEV (local exhaust ventilation): 95 % (inhalative).

Number of the contributing scenario

8

Contributing exposure scenario controlling worker exposure for PROC 9

Frequency and duration of use

8 h (full shift)

Other given operational conditions affecting workers exposure

Indoor use

Technical conditions and measures to control dispersion from source towards the worker

Provide a basic standard of general ventilation (1 to 3 air changes per hour). Effectiveness of LEV (local exhaust ventilation): 90 % (inhalative).

Exposure estimation and reference to its source

Environment

PEC = predicted environmental concentration (local); RCR = risk characterisation ratio

| | |
|-----------------------------------|-----------------------------------|
| Fresh Water (Pelagic) | PEC: 4.28E-3 mg/l; RCR: 0.052 |
| Fresh Water (Sediment) | PEC: 0.017 mg/kg dw; RCR: 0.052 |
| Marine Water (Pelagic) | PEC: 4.88E-4 mg/l; RCR: 0.06 |
| Marine Water (Sediment) | PEC: 1.93E-3 mg/kg dw; RCR: 0.059 |
| Agricultural Soil | PEC: 3.06E-3 mg/kg dw; RCR: 0.184 |
| Sewage Treatment Plant (Effluent) | PEC: 0 mg/l; RCR: < 0.01 |

Human exposure prediction (oral, dermal, inhalative)

Oral exposure is not expected to occur. EE(inhal): Estimated inhalative long-term exposure [mg/m³]. The RMMs described above suffice to control risks for both local and systemic effects.

| | |
|---------|------------------|
| Proc 1 | EE(inhal): 0.031 |
| Proc 2 | EE(inhal): 15.44 |
| Proc 3 | EE(inhal): 30.88 |
| Proc 8a | EE(inhal): 15.44 |
| Proc 8b | EE(inhal): 3.861 |
| Proc 9 | EE(inhal): 15.44 |

Risk characterisation

RCR(inhal): inhalative risk characterisation ratio. Where required local and systemic effects were evaluated both for short-term and long-term exposure. The RCR's given correspond in each case to the most conservative calculated values.

| | |
|---------|--------------------|
| Proc 1 | RCR(inhal): < 0.01 |
| Proc 2 | RCR(inhal): 0.05 |
| Proc 3 | RCR(inhal): 0.1 |
| Proc 8a | RCR(inhal): 0.05 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended



n-Butanol
10420

Version / Revision 5

Proc 8b
Proc 9

RCR(inhal): 0.012
RCR(inhal): 0.05

Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

For specific information regarding the SPERC used please refer to the ESIG webpage
<https://www.esig.org/reach-ges/environment/>

associated uses:

Should consumer uses be associated with this exposure scenario, please contact OQ for further details
Other combinations of operational conditions may also be safe. Please contact OQ in case your local operational conditions differ from the ones described above and you are unsure if they are also safe